

## Specification Sheet

Part Number: 596-00987

Made with UV-stable inks and materials for durability and weather resistance.

Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.

High abrasion and scuff resistance for high-performance labeling.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

### ENERGY STORAGE SYSTEM DC DISCONNECT

NOMINAL ESS VOLTAGE:

MAX. AVAILABLE

SHORT CIRCUIT CURRENT:

Solar Label, Printable, ENERGY STORAGE...DISCONNECT, 3.75" x 2.12", PET, Red, 50/roll

**Article Number** 596-00987

**Type** MBSDIS

**Color** Red (RD)

**Quantity Per** roll

**Product Description** Designed with cross-laminated UV stable materials, these variable print solar installation labels are designed to accept printing from any standard thermal transfer printer using a resin-based ink ribbon for the best durability. Print your voltage information directly on the label and then laminate with an optional clear acrylic laminate material for added protection. These labels can be used to print disconnecting means and breaker series directly on the labels for a more professional result and a smoother inspection process.

<b>Short Description</b>	Solar Label, Printable, ENERGY STORAGE...DISCONNECT, 3.75" x 2.12", PET, Red, 50/roll
<b>Global Part Name</b>	MBSDIS-840/281-RD
<b>Technical Description</b>	Printable Solar Label, 2017 Code, ENERGY STORAGE...DISCONNECT, 3.75" x 2.12", Polyester, Red
<b>Width W (Imperial)</b>	3.75
<b>Width W (Metric)</b>	95.25
<b>Thickness T (Imperial)</b>	0.0025
<b>Thickness T (Metric)</b>	64.0
<b>Height H (Imperial)</b>	2.12
<b>Height H (Metric)</b>	53.8
<b>Material</b>	Type 840/281, Polyester, UV-stabilized, clear polyester laminate (840/281)
<b>Material Shortcut</b>	840/281
<b>Adhesive</b>	Acrylic
<b>Halogen Free</b>	Yes

<b>Adhesive Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	UL 969 NEC2020 CSA 66956 NEC2017 IFC 2012
<b>Warranty (US)</b>	Yes
<b>UL Recognized (US)</b>	Yes
<b>Package Quantity (Imperial)</b>	50
<b>Package Quantity (Metric)</b>	50
<b>Customs Number</b>	3919102055
<b>Labels per Column</b>	1
<b>Labels per Row</b>	1