



## Main

|                             |  |
|-----------------------------|--|
| Range                       | Spacial  |
| Product name                | Spacial S3DB                                     |
| Application                 | Terminal application                             |
| Category                    | Compact enclosure                                |
| Enclosure nominal height    | 9.84 in (250 mm)                                 |
| Enclosure nominal width     | 15.75 in (400 mm)                                |
| Enclosure nominal depth     | 5.91 in (150 mm)                                 |
| Door type                   | Solid  |
| Mounting plate description  | Without mounting plate                           |
| Type of gland plate         | Without gland plate                              |
| Installation accessory type | Horizontal or vertical position<br>Wall-mounting |
| Product destination         | For equipping with terminal                      |
| Device composition          | 1 body<br>1 door<br>1 lock                       |

## Complementary

|                             |  |
|-----------------------------|--|
| Body type                   | Single piece body<br>Gutter-shaped front rail double sheet thickness |
| Number of doors             | Front face 1   |
| Door opening side           | Reversible 180 °)  |
| Lock type                   | 3 mm double-bar lock   |
| Accessibility for operation | Front  |
| Removable parts             | Door by hinges   |
| Material                    | steel  |
| Surface finish              | Epoxy-polyester powder   |
| Color                       | Gray RAL 7035)   |
| Standards                   | IEC 62208  |
| Product Certifications      | CUL<br>LR<br>GL<br>UL<br>BV<br>DNV                                   |
| Net Weight                  | 9.11 lb(US) (4.13 kg)  |

## Environment

|                           |                |
|---------------------------|----------------|
| NEMA Degree of Protection | NEMA 4X/13     |
| IK degree of protection   | IK10 IEC 62262 |
| IP degree of protection   | IP66 IEC 60529 |

## Ordering and shipping details

|                       |  |
|-----------------------|--|
| Category              | 80034-ENCLOSURE SYSTEMS WALL MOUNT METAL |
| Discount Schedule     | ES1                                      |
| GTIN                  | 3606480158810                            |
| Nbr. of units in pkg. | 1  |
| Package weight(Lbs)   | 9.22 lb(US) (4.18 kg)                    |
| Returnability         | No                                       |
| Country of origin     | FR                                       |

## Packing Units

|                              |                          |
|------------------------------|--------------------------|
| Unit Type of Package 1       | PCE                      |
| Package 1 Height             | 6.50 in (16.5 cm)        |
| Package 1 width              | 7.68 in (19.5 cm)        |
| Package 1 Length             | 16.34 in (41.5 cm)       |
| Unit Type of Package 2       | PAM                      |
| Number of Units in Package 2 | 84                       |
| Package 2 Weight             | 813.51 lb(US) (369.0 kg) |
| Package 2 Height             | 82.68 in (210.0 cm)      |
| Package 2 width              | 39.37 in (100.0 cm)      |
| Package 2 Length             | 47.24 in (120.0 cm)      |

## Offer Sustainability

|                            |  |
|----------------------------|--|
| Sustainable offer status   | Green Premium product  |
| REACH Regulation           | <a href="#">REACH Declaration</a>  |
| REACH free of SVHC         | Yes  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes  |
| RoHS exemption information | <a href="#">Yes</a>  |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|