

► Customized Length ► Post-processing

Heat sinks are essential components in thermal management assemblies and are used to dissipate heat to the environment. Usually manufactured from highly thermally conductive aluminum or copper alloys, they are lightweight, easy to machine and can be produced in a range of profiles. The typical finned profiles have large surface areas which increases the heat sink's ability to dissipate heat via convection. T-Global carry a range of off the shelf profiles for most projects and can manufacture custom sizes for bespoke applications.

► The specifications are all in width × length × height ► These are regular sizes

<p>TGH-0075-01</p> <table border="1"> <tr> <td>7.5×7.5×10mm</td> <td>1g</td> </tr> <tr> <td>Clean</td> <td>AL6063</td> </tr> </table>	7.5×7.5×10mm	1g	Clean	AL6063	<p>TGH-0100-01</p> <table border="1"> <tr> <td>10×10×9.5mm</td> <td>1.5g</td> </tr> <tr> <td>Clean</td> <td>AL6063</td> </tr> </table>	10×10×9.5mm	1.5g	Clean	AL6063	<p>TGH-0124-01</p> <table border="1"> <tr> <td>12.4×12.4×13mm</td> <td>3g</td> </tr> <tr> <td>Black Anodized</td> <td>AL6063</td> </tr> </table>	12.4×12.4×13mm	3g	Black Anodized	AL6063	<p>TGH-0130-01</p> <table border="1"> <tr> <td>13×13×6mm</td> <td>2g</td> </tr> <tr> <td>Clean</td> <td>AL6063</td> </tr> </table>	13×13×6mm	2g	Clean	AL6063
7.5×7.5×10mm	1g																		
Clean	AL6063																		
10×10×9.5mm	1.5g																		
Clean	AL6063																		
12.4×12.4×13mm	3g																		
Black Anodized	AL6063																		
13×13×6mm	2g																		
Clean	AL6063																		
<p>Recommended thermal tape</p> <p>TG-T1000-5.5-5.5-0.25-5PT</p>	<p>Recommended thermal tape</p> <p>TG-T1000-8-8-0.25-5PT</p>	<p>Recommended thermal tape</p> <p>TG-T1000-10.4-10.4-0.25-5PT</p>	<p>Recommended thermal tape</p> <p>TG-T1000-11-11-0.25-5PT</p>																
<p>TGH-0130-02</p> <table border="1"> <tr> <td>13×13×9mm</td> <td>2g</td> </tr> <tr> <td>Black Anodized</td> <td>AL6063</td> </tr> </table>	13×13×9mm	2g	Black Anodized	AL6063	<p>TGH-0130-03</p> <table border="1"> <tr> <td>13×35×6mm</td> <td>4g</td> </tr> <tr> <td>Black Anodized</td> <td>AL6063</td> </tr> </table>	13×35×6mm	4g	Black Anodized	AL6063	<p>TGH-0132-01</p> <table border="1"> <tr> <td>13.2×19×9.7mm</td> <td>1.5g</td> </tr> <tr> <td>Black Anodized</td> <td>AL1050</td> </tr> </table>	13.2×19×9.7mm	1.5g	Black Anodized	AL1050	<p>TGH-0137-02</p> <table border="1"> <tr> <td>13.7×25.6×12mm</td> <td>2g</td> </tr> <tr> <td>Black Anodized</td> <td>AL1050</td> </tr> </table>	13.7×25.6×12mm	2g	Black Anodized	AL1050
13×13×9mm	2g																		
Black Anodized	AL6063																		
13×35×6mm	4g																		
Black Anodized	AL6063																		
13.2×19×9.7mm	1.5g																		
Black Anodized	AL1050																		
13.7×25.6×12mm	2g																		
Black Anodized	AL1050																		
<p>Recommended thermal tape</p> <p>TG-T1000-11-11-0.25-5PT</p>	<p>Recommended thermal tape</p> <p>TG-T1000-33-11-0.25-5PT</p>	<p>Recommended thermal tape</p> <p>TG-T1000-17-11.2-0.25-5PT</p>	<p>Recommended thermal tape</p> <p>TG-T1000-23.6-11.7-0.25-5PT</p>																
<p>TGH-0160-01</p> <table border="1"> <tr> <td>16×16×11mm</td> <td>3g</td> </tr> <tr> <td>Clean</td> <td>AL6063</td> </tr> </table>	16×16×11mm	3g	Clean	AL6063	<p>TGH-0164-01</p> <table border="1"> <tr> <td>16.4×16×10mm</td> <td>3g</td> </tr> <tr> <td>Black Anodized</td> <td>AL6063</td> </tr> </table>	16.4×16×10mm	3g	Black Anodized	AL6063	<p>TGH-0170-01</p> <table border="1"> <tr> <td>17×17×9.5mm</td> <td>3g</td> </tr> <tr> <td>Black Anodized</td> <td>AL6063</td> </tr> </table>	17×17×9.5mm	3g	Black Anodized	AL6063	<p>TGH-0190-01</p> <table border="1"> <tr> <td>19×19×5mm</td> <td>3g</td> </tr> <tr> <td>Black Anodized</td> <td>AL6063</td> </tr> </table>	19×19×5mm	3g	Black Anodized	AL6063
16×16×11mm	3g																		
Clean	AL6063																		
16.4×16×10mm	3g																		
Black Anodized	AL6063																		
17×17×9.5mm	3g																		
Black Anodized	AL6063																		
19×19×5mm	3g																		
Black Anodized	AL6063																		
<p>Recommended thermal tape</p> <p>TG-T1000-14-14-0.25-5PT</p>	<p>Recommended thermal tape</p> <p>TG-T1000-14.4-14-0.25-5PT</p>	<p>Recommended thermal tape</p> <p>TG-T1000-15-15-0.25-5PT</p>	<p>Recommended thermal tape</p> <p>TG-T1000-17-17-0.25-5PT</p>																

T-Global Technology (Europe & North America) Limited

Units 1-2 Cosford Business Park, Central Park, Lutterworth, Leicestershire, LE17 4QU, United Kingdom
T +44 (0)1455 553 510 **E** sales@tglobaltechnology.com **W** www.tglobaltechnology.com


Version17
20210305




T-Global Technology are proud to announce the launch of a new company logo and mission statement as part of the ongoing growth and evolution of our company's brand.

NOTICE: The information contained herein is to the best of our knowledge true and accurate. Values stated in this technical data sheet represent typical values as not all tests are run on each lot of material produced. All specifications are subject to change without notice. The protective film does not affect the function of the product. If there is no special requirement, the default depends on T-Global. Since the varied conditions of potential use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part and users should make their own test to determine the suitability of our products in any specific situation. This product is sold without warranty either expressed or implied, of fitness for a particular purpose or otherwise, except that this product shall be of standard quality, and except to the extent otherwise stated in T-Global Technology's invoice, quotation, or order acknowledgment. We disclaim any and all liabilities incurred in connection with the use of information contained herein, or otherwise. All risks of such are assumed by the user. Furthermore, nothing contained herein shall be construed as a recommendation to use any process or to manufacture or to use any product in conflict with existing or future patents covering any product or material or its use.


► The specifications are all in width × length × height ► These are regular sizes




TGH-0200-02	
20×20×6mm	4g
Black Anodized	AL6063
Recommended thermal tape	
TG-T1000-18-18-0.25-5PT	




TGH-0200-03	
20×20×9.5mm	4g
Anodizing aluminum color	AL6063
Recommended thermal tape	
TG-T1000-18-18-0.25-5PT	




TGH-0200-05	
20×33×9.5mm	8g
Black Anodized	AL1050
Recommended thermal tape	
TG-T1000-31-18-0.25-5PT	




TGH-0200-06	
20×44×6mm	9g
Clean	AL1050
Recommended thermal tape	
TG-T1000-42-18-0.25-5PT	




TGH-0210-01	
21×25×3.5mm	3g
Anodizing aluminum color	AL6063
Recommended thermal tape	
TG-T1000-23-19-0.25-5PT	




TGH-0220-02	
22×15×11.7mm	4g
Black Anodized	AL6063
Recommended thermal tape	
TG-T1000-20-13-0.25-5PT	




TGH-0220-03	
22×22×9mm	5g
Black Anodized	AL6063
Recommended thermal tape	
TG-T1000-20-20-0.25-5PT	




TGH-0220-04	
22×22×11.7mm	7g
Black Anodized	AL6063
Recommended thermal tape	
TG-T1000-20-20-0.25-5PT	




TGH-0220-06	
22×27×9mm	6g
Black Anodized	AL6063
Recommended thermal tape	
TG-T1000-25-20-0.25-5PT	




TGH-0220-07	
22×45×14.5mm	23g
Anodizing aluminum color	AL6063
Recommended thermal tape	
TG-T1000-43-20-0.25-5PT	




TGH-0250-01	
25×25×9mm	9g
Anodizing aluminum color	AL6063
Recommended thermal tape	
TG-T1000-23-23-0.25-5PT	




TGH-0260-02	
26×26×14.8mm	10g
Anodizing aluminum color	AL6063
Recommended thermal tape	
TG-T1000-24-24-0.25-5PT	




TGH-0280-01	
28×20×4.5mm	4g
Black Anodized	AL6063
Recommended thermal tape	
TG-T1000-26-18-0.25-5PT	



TGH-0280-02	
28×28×4.5mm	5g
Black Anodized	AL6063
Recommended thermal tape	
TG-T1000-26-26-0.25-5PT	



TGH-0280-04	
28×28×8mm	8g
Black Anodized	AL6063
Recommended thermal tape	
TG-T1000-26-26-0.25-5PT	



TGH-0280-05	
28×28×11.4mm	10g
Black Anodized	AL6063
Recommended thermal tape	
TG-T1000-26-26-0.25-5PT	

T-Global Technology (Europe & North America) Limited

Units 1-2 Cosford Business Park, Central Park, Lutterworth, Leicestershire, LE17 4QU, United Kingdom
T +44 (0)1455 553 510 **E** sales@tglobaltechnology.com **W** www.tglobaltechnology.com


Version17
20210305




T-Global Technology are proud to announce the launch of a new company logo and mission statement as part of the ongoing growth and evolution of our company's brand.

NOTICE: The information contained herein is to the best of our knowledge true and accurate. Values stated in this technical data sheet represent typical values as not all tests are run on each lot of material produced. All specifications are subject to change without notice. The protective film does not affect the function of the product. If there is no special requirement, the default depends on T-Global. Since the varied conditions of potential use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part and users should make their own test to determine the suitability of our products in any specific situation. This product is sold without warranty either expressed or implied, of fitness for a particular purpose or otherwise, except that this product shall be of standard quality, and except to the extent otherwise stated in T-Global Technology's invoice, quotation, or order acknowledgment. We disclaim any and all liabilities incurred in connection with the use of information contained herein, or otherwise. All risks of such are assumed by the user. Furthermore, nothing contained herein shall be construed as a recommendation to use any process or to manufacture or to use any product in conflict with existing or future patents covering any product or material or its use.


► The specifications are all in width × length × height ► These are regular sizes




TGH-0280-06	
28×28×12.7mm	12g
Black Anodized	AL6063
Recommended thermal tape	
TG-T1000-26-26-0.25-5PT	




TGH-0280-07	
28×28×15mm	16g
Anodizing aluminum color	AL6063
Recommended thermal tape	
TG-T1000-26-26-0.25-5PT	




TGH-0280-08	
28×28×22mm	20g
Black Anodized	AL6063
Recommended thermal tape	
TG-T1000-26-26-0.25-5PT	




TGH-0300-01	
30×30×6.6mm	6g
Anodizing aluminum color	AL6063
Recommended thermal tape	
TG-T1000-28-28-0.25-5PT	




TGH-0300-03	
30×30×12mm	12g
Golden Anodized	AL6063
Recommended thermal tape	
TG-T1000-28-28-0.25-5PT	




TGH-0300-04	
30×30×15mm	13g
Anodizing aluminum color	AL6063
Recommended thermal tape	
TG-T1000-28-28-0.25-5PT	




TGH-0325-01	
32.5×32.5×27.5mm	21g
Black Anodized	AL6063
Recommended thermal tape	
TG-T1000-30.5-30.5-0.25-5PT	




TGH-0350-03	
35×35×15mm	24g
Black Anodized	AL6063
Recommended thermal tape	
TG-T1000-33-33-0.25-5PT	




TGH-0350-04	
35×35×20mm	30g
Black Anodized	AL6063
Recommended thermal tape	
TG-T1000-33-33-0.25-5PT	




TGH-0380-01	
38×20×9mm	10g
Clean	AL6063
Recommended thermal tape	
TG-T1000-36-18-0.25-5PT	




TGH-0380-03	
38×38×9mm	19g
Black Anodized	AL6063
Recommended thermal tape	
TG-T1000-36-36-0.25-5PT	




TGH-0380-05	
38×38×15mm	19g
Clean	AL6063
Recommended thermal tape	
TG-T1000-36-36-0.25-5PT	




TGH-0400-01	
40×40×10mm	24g
Black Anodized	AL6063
Recommended thermal tape	
TG-T1000-38-38-0.25-5PT	



TGH-0400-03	
40×40×11mm	17g
Black Anodized	AL6063
Recommended thermal tape	
TG-T1000-38-38-0.25-5PT	



TGH-0400-04	
40×40×20mm	26g
Black Anodized	AL6063
Recommended thermal tape	
TG-T1000-38-38-0.25-5PT	



TGH-0450-01	
45×45×10mm	27g
Black Anodized	AL6063
Recommended thermal tape	
TG-T1000-43-43-0.25-5PT	

T-Global Technology (Europe & North America) Limited

Units 1-2 Cosford Business Park, Central Park, Lutterworth, Leicestershire, LE17 4QU, United Kingdom
T +44 (0)1455 553 510 **E** sales@tglobaltechnology.com **W** www.tglobaltechnology.com


Version17
20210305




T-Global Technology are proud to announce the launch of a new company logo and mission statement as part of the ongoing growth and evolution of our company's brand.

NOTICE: The information contained herein is to the best of our knowledge true and accurate. Values stated in this technical data sheet represent typical values as not all tests are run on each lot of material produced. All specifications are subject to change without notice. The protective film does not affect the function of the product. If there is no special requirement, the default depends on T-Global. Since the varied conditions of potential use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part and users should make their own test to determine the suitability of our products in any specific situation. This product is sold without warranty either expressed or implied, of fitness for a particular purpose or otherwise, except that this product shall be of standard quality, and except to the extent otherwise stated in T-Global Technology's invoice, quotation, or order acknowledgment. We disclaim any and all liabilities incurred in connection with the use of information contained herein, or otherwise. All risks of such are assumed by the user. Furthermore, nothing contained herein shall be construed as a recommendation to use any process or to manufacture or to use any product in conflict with existing or future patents covering any product or material or its use.


► The specifications are all in width × length × height ► These are regular sizes




TGH-0500-01	
50×50×17mm	56g
Anodizing aluminum color	AL6063
Recommended thermal tape	
TG-T1000-48-48-0.25-5PT	




TGH-0510-01	
51×35×5mm	17g
Black Anodized	AL6063
Recommended thermal tape	
TG-T1000-49-33-0.25-5PT	




TGH-0510-02	
51×100×20mm	113g
Anodizing aluminum color	AL6063
Recommended thermal tape	
TG-T1000-98-49-0.25-5PT	




TGH-0522-01	
52.2×52.2×23mm	74g
Anodizing aluminum color	AL6063
Recommended thermal tape	
TG-T1000-50.2-50.2-0.25-5PT	




TGH-0550-01	
55×55×6mm	32g
Anodizing aluminum color	AL6063
Recommended thermal tape	
TG-T1000-53-53-0.25-5PT	



TGH-0610-01	
61×61×13mm	67g
Anodizing aluminum color	AL6063
Recommended thermal tape	
TG-T1000-59-59-0.25-5PT	



TGH-0955-01	
95.5×95×14.3mm	134g
Black Anodized	AL6063
Recommended thermal tape	
TG-T1000-93.5-93-0.25-5PT	



TGH-1535-01	
153.5×150×34mm	906g
Anodizing aluminum color	AL6063
Recommended thermal tape	
TG-T1000-151.5-148-0.25-5PT	

T-Global Technology (Europe & North America) Limited

Units 1-2 Cosford Business Park, Central Park, Lutterworth, Leicestershire, LE17 4QU, United Kingdom
T +44 (0)1455 553 510 **E** sales@tglobaltechnology.com **W** www.tglobaltechnology.com

Version17
20210305



T-Global Technology are proud to announce the launch of a new company logo and mission statement as part of the ongoing growth and evolution of our company's brand.

NOTICE: The information contained herein is to the best of our knowledge true and accurate. Values stated in this technical data sheet represent typical values as not all tests are run on each lot of material produced. All specifications are subject to change without notice. The protective film does not affect the function of the product. If there is no special requirement, the default depends on T-Global. Since the varied conditions of potential use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part and users should make their own test to determine the suitability of our products in any specific situation. This product is sold without warranty either expressed or implied, of fitness for a particular purpose or otherwise, except that this product shall be of standard quality, and except to the extent otherwise stated in T-Global Technology's invoice, quotation, or order acknowledgment. We disclaim any and all liabilities incurred in connection with the use of information contained herein, or otherwise. All risks of such are assumed by the user. Furthermore, nothing contained herein shall be construed as a recommendation to use any process or to manufacture or to use any product in conflict with existing or future patents covering any product or material or its use.