

## Specification Sheet

Part Number: 157-00367

Off-Set design allows bundles to sit off of mounting points to avoid friction against surrounding areas.

Fir tree gives 3 to 1 extraction versus insertion force making them strong and easy to install.

Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.



1-Pc Cable Tie/Fir Tree Mount w/Disc, 12.5mm Offset, 8.5"L, 6.1-7mm Hole, PA66HIRHSUV, Black, 3000/ctn

<b>Article Number</b>	157-00367
<b>Type</b>	T50ROSFT6SO12.5A
<b>Color</b>	Black (BK)
<b>Quantity Per</b>	bag

**Product Description**

HellermannTyton's Off-Set Fir Tree Cable Tie and fixing offers a simple and easy to use method of bundling and fixing cables, the design of the fir tree ensures a positive and secure fixing into panels with thicknesses from .2" - .26" or threaded blind holes. The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

**Short Description**

1-Pc Cable Tie/Fir Tree Mount w/Disc, 12.5mm Offset, 8.5"L, 6.1-7mm Hole, PA66HIRHSUV, Black, 3000/ctn

**Global Part Name**

T50ROSFT6SO12.5A-PA66HIRHSUV-BK

**Minimum Tensile Strength (Imperial)** 50.0

**Minimum Tensile Strength (Metric)** 225.0

**Length L (Imperial)** 8.5

**Length L (Metric)** 215.9

**Offset Length (Imperial)** 0.49

**Offset Length (Metric)** 12.5

**Fixation Method** Fir Tree

**Identification Plate Position** none

**Releasable Closure** No

**Width W (Imperial)** 0.19

**Width W (Metric)** 5.1

**Bundle Diameter Min (Imperial)** 0.08

**Bundle Diameter Min (Metric)** 2.0

**Bundle Diameter Max (Imperial)** 1.97

**Bundle Diameter Max (Metric)** 50.0

<b>Height H (Imperial)</b>	0.87
<b>Panel Thickness Min (Imperial)</b>	0.02
<b>Panel Thickness Max (Imperial)</b>	0.26
<b>Panel Thickness Min (Metric)</b>	0.6
<b>Panel Thickness Max (Metric)</b>	6.65
<b>Mounting Hole Diameter D (Imperial)</b>	0.24 - 0.28 ";0.24 - 0.26
<b>Mounting Hole Diameter D (Metric)</b>	6.1 - 7.0 mm 6.35 mm (hexagonal)
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.24
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.28 ";0.26
<b>Mounting Hole Diameter D Max (Metric)</b>	7.0
<b>Disc Diameter (Metric)</b>	15.0
<b>Disc Diameter (Imperial)</b>	0.59
<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)

<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	3000
<b>Package Quantity (Metric)</b>	3000
<b>Customs Number</b>	3926909988