

## Item description

PIO3 hardware configuration

- 2 x ETHERNET port for connecting to field devices and the engineering tool
- 2 x USB port for optional connection of a USB stick, mouse or keyboard
- Audio interface for connecting a headphone or loudspeaker
- CAN for controlling field devices
- RS-232/485 interface for controlling field devices equipped with a serial interface
- 4 x digital input/output for reading/triggering digital signals
- Power-failure-proof storage component

## Data

### Technical data

Display diagonal	14.5 cm (5.7 inches)
Display	Resistive touchscreen
Display colors	262,000 colors
Graphics resolution	(640 x 480) px
Contrast ratio	300:1
Viewing angle (horizontal/vertical)	80° / 80°
Brightness	630 cd/m <sup>2</sup>
Visualization	Web server Web-Visu Webserver Web Visu Target Visu

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
 Hansastr. 27  
 32423 Minden  
 Phone: +49571 887-0 | Fax: +49571 887-169  
 Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
 We are always happy to take your call at +49 (571) 887-44222.



ETHERNET protocols	DHCP DNS FTP FTPS HTTP HTTPS SSH
Communication	Web browser Web browser (HTML5) Modbus TCP master/slave Modbus (UDP), WagoAppPlcModbus Library Modbus (RTU), WagoAppPlcModbus Library ETHERNET EtherNet/IP™ Adapter (slave) EtherNet/IP™ Scanner CANopen EtherCAT® Master OPC UA Server/Client OPC UA Pub/Sub (can be installed later) MQTT RS-232 serial interface RS-485 interface BACnet/IP, <b>requires an additional license</b> Telecontrol protocols, <b>requires an additional license</b> MicroBrowser (Visualization of CODESYS V2.3), requires an additional license
Operating system	Real-time Linux (with RT-Preempt patch)
Processor	ARM® Cortex® A9 Quadcore 1.0 GHz
Programming environment	CODESYS V3.5, from firmware release 24 <i>e!COCKPIT</i> (based on CODESYS V3), up to firmware release 22
Main memory (RAM)	2,048 MB
Internal memory (flash)	4096 MB
Program memory	32 MB
Data memory	128 MB
Non-volatile software memory	128. Kbytes
Type of memory card	microSD (max. 2 GB); microSDHC (max. 32 GB)
Indicators	Three-color LED (red, green, blue)
Controls	Resistive touch panel; 2 capacitive keys; proximity sensor
Supply voltage	24 VSELV DC (18 ... 31.2 V); with reverse voltage protection
Operating power	7.0 W, without USB load; 12.0 W, with USB load

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



## Connection data

Connection technology: communication/fieldbus	Modbus (TCP, UDP): 2 x RJ-45; EtherNet/IP™: 2 x RJ-45; CANopen: 1 x D-sub 9 plug; Modbus (UDP): 2 x RJ-45; RS-232 + RS-485/422 serial interface: 1 x D-sub 9 socket; USB: 2 x USB 2.0 host (type A)
Connection technology: supply	1 x included female connector (734-103) with three CAGE CLAMP® connections

## Physical data

Width	172 mm / 6.772 inches
Height	163 mm / 6.417 inches
Depth	78 mm / 3.070 inches
Panel cutout (W x H)	(157 x 148) mm

## Mechanical Data

Weight	1221 g
--------	--------

## Environmental requirements

Ambient temperature (operation)	-20 ... +55 °C (when mounted vertically; -20 ... +50 °C, other mounting positions)
Ambient temperature (storage)	-20 ... +80 °C
Protection type	IP65
Note on protection type	IP65 (front side); IP20 (rear side), per EN 60529
Relative humidity (without condensation)	90 %
Mounting type	Clamping elements (included) or VESA mount (4 x M4x8)
Fire load	0.003 MJ

## Commercial data

ETIM 8.0	EC001414
ETIM 7.0	EC001414
PU (SPU)	1 pcs
Packaging type	box
Country of origin	DE
GTIN	4055143839464
Customs tariff number	84714100000

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.




## Environmental Product Compliance

RoHS Compliance Status


Compliant, No Exemption

## Approvals / Certificates


### General approvals

Logo	Approval	Additional Approval Text	Certificate name
	EAC Brjansker Zertifizierungsstelle	TP TC 020/2011	EAC RU C-DE.AM02.B.00087/19
	KC National Radio Research Agency	Article 58-2, Clause 3	MSIP-REM-W43-WBP762
	UL Underwriters Laboratories Inc. (ORDINARY LOCATIONS)	UL 61010-2-201	E175199

### Declarations of conformity and manufacturer's declarations

Logo	Approval	Additional Approval Text	Certificate name
	EU-Declaration of Conformity WAGO GmbH & Co. KG	-	-

### Approvals for marine applications

Logo	Approval	Additional Approval Text	Certificate name
	DNV DNV Germany GmbH	DNV-CG-0339, Aug. 2021	TAA00001FS

## Optional accessories

### Memory card

Memory card



Item no.: 758-879/000-3102  
Memory Card SD Micro; 2 GByte

[www.wago.com/758-879/000-3102](http://www.wago.com/758-879/000-3102)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



Item no.: 758-879/000-3108

Memory Card SD Micro; pSLC-NAND; 8 GB; Temperature range: -40 to 90°C

[www.wago.com/758-879/000-3108](http://www.wago.com/758-879/000-3108)

## Software

Software applications



Item no.: 2759-208/211-1000

Library MTP; Single License; Online activation

[www.wago.com/2759-208/211-1000](http://www.wago.com/2759-208/211-1000)

## Mounting

Mounting accessories



Item no.: 762-9001

e!DISPLAY7300T ; Clamping elements (4 pieces)

[www.wago.com/762-9001](http://www.wago.com/762-9001)

## Downloads

### Documentation

#### Manual

Product Manual WAGO Touch Panel 600 Standard Line	1.7.0 2022 May 24	pdf 2.5 MB	Download
--	----------------------	---------------	----------

Product Manual OPC UA Mapping Editor	V 1.1.0 2022 Mar 11	pdf 3.4 MB	Download
--------------------------------------	------------------------	---------------	----------

OPC_UA Mapping Editor Online Help HTML		URL	Download
---	--	-----	----------

Migration Guide from e!COCKPIT projects to CODESYS V3.5 Online Help (HTML)		URL	Download
---	--	-----	----------

#### Bid Text

762-4302/8000-002 X81 - Datei	2019 Feb 19	xml 6.1 kB	Download
----------------------------------	-------------	---------------	----------

762-4302/8000-002 docx - Datei	2019 Jan 4	docx 22.7 kB	Download
-----------------------------------	------------	-----------------	----------

ausschreiben.de 762-4302/8000-002		URL	Download
-----------------------------------	--	-----	----------

#### Tutorial

Establish connection to a controller using SSH	1.0	mp4	Download
--	-----	-----	----------

Subject to changes. Please also observe the further product documentation!



In this video we are demonstrating how to establish a SSH connection with a controller using for example PuTTY to be able to work with the LINUX console. Contents: 0:21 Download and install the SSH client; 0:40 Establish the SSH connection; 0:50 Log on to the Controller

2017 Aug 5

29.0 MB

### System Description

Touch Panel 600, system description

pdf  
151.9 kB

Download

### Additional Information

WAGO OPC UA Server

V 1.1.0  
2021 Jan 28

pdf  
1.2 MB

Download

### Application Notes

#### Application Note e!COCKPIT

e!COCKPIT Application Note WAGO Visualization Datalogger (a2022005)  
WAGO Visualization Datalogger is a Web application that can be used as a visualization tool for the recorded data of the datalogger library (WAGOAppDatalogger).  
WAGO Visualization Datalogger does not replace the datalogger but is rather a supplementary function. It is an HTML/Javascript application available via the Webserver on the controller. The user launches the Web application in a browser.

20230505  
2023 May 5

zip  
4.1 MB

Download

e!COCKPIT Anwendungshinweis HVAC BACnet Macros (a2021010)  
Basierend auf der Bibliothek WagoAppBuildingHVAC\_BACnet stellt WAGO in dem Bereich Heizung, Lüftung und Klimatisierung verschieden HLK-Anlagenmakros mit BACnet-Anbindung zur Verfügung.

1.3.0  
2023 Feb 27

zip  
69.2 MB

Download

### Engineering-Software

#### e!COCKPIT

e!COCKPIT  
Register at no cost and test our engineering software for 30 days.

1.11.2.0  
2023 Apr 24

zip  
4.1 GB

Download

#### WAGO Solution Builder

WAGO Solution Builder

URL

Download

WAGO Solution Builder is a software solution that enables holistic and efficient building automation project engineering and can be used throughout the entire building life cycle. With WAGO Solution Builder, you can organize all of your own building automation projects on a web interface and, thanks to integrated device management, ensure that your project-specific WAGO controllers are always updated.

Subject to changes. Please also observe the further product documentation!



Once downloaded, the software can be used for free during the launch phase until October 2023. After that, you can activate WAGO Solution Builder by purchasing a license key.

## Desktop Application

WAGUpload	URL	Download
WAGUpload is a stand-alone PC software for transferring, backing up and restoring PLC applications on WAGO 750 Series controllers.		

## Runtime Software

### Firmware

Image Update (SD Karte) TP 600 WAGO_FW0762-4xxx_V031010_IX22_SP1_I	V 22 SP1 2022 Dec 14	zip 220.8 MB	Download
WUP Update (WAGUpload Tool) TP 600 WAGO_FW0762-4xxx_V031010_IX22_SP1_W	V 22 SP1 2022 Dec 14	zip 219.0 MB	Download

## CAD/CAE-Data

### CAD data

2D/3D Models 762-4302/8000-002	URL	Download
--------------------------------	-----	----------

### CAE data

ZUKEN Portal 762-4302/8000-002	URL	Download
EPLAN Data Portal 762-4302/8000-002	URL	Download

## Environmental Product Compliance

### Compliance Search

Environmental Product Compliance 762-4302/8000-002 Touch Panel 600; 14.5 cm (5.7"); 640 x 480 pixels; 2 x ETHERNET, 2 x USB, CAN, DI /DO, RS-232/485, Audio; Control Panel	URL	Download
---	-----	----------

## Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.





## Product family

### Standard Line

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!

---

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.