


# Termination resistor - SAC-5P-M12MS PB TR - 1507803

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Terminating resistor PROFIBUS M12

## Key Commercial Data

Packing unit	5 pc
GTIN	 4 017918 900403
GTIN	4017918900403

## Technical data

### Ambient conditions

Ambient temperature (operation)	-25 °C ... 90 °C (Plug)
---------------------------------	-------------------------

### General

Rated current at 40°C	4 A
	≤ 25 mA ( $I_{eff}$ )
Rated voltage	48 V AC
	60 V DC
	5 V <sub>rms</sub>
Termination resistor	390 Ω ±1 % (R1)
	220 Ω ±1 % (R2)
	390 Ω ±1 % (R3)
Power consumption	0.25 W (R1)
	0.25 W (R2)
	0.25 W (R3)
Number of positions	4
Insulation resistance	≥ 100 MΩ
Coding	B - inverse
Status display	No

# Termination resistor - SAC-5P-M12MS PB TR - 1507803

## Technical data

### General

Overvoltage category	II
Degree of pollution	3
Insertion/withdrawal cycles	≥ 100
Torque	0.4 Nm (M12 connector)

### Material

Flammability rating according to UL 94	HB
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material of grip body	TPU, hardly inflammable, self-extinguishing
Material, knurls	Zinc die-cast, nickel-plated

### Standards and Regulations


Flammability rating according to UL 94	HB
--	----

### Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

## Drawings


Dimensional drawing



Plug, M12 x 1, straight, shielded

## Termination resistor - SAC-5P-M12MS PB TR - 1507803


Circuit diagram



Contact assignment of the termination resistor; for resistance values, see technical data

# Termination resistor - SAC-5P-M12MS PB TR - 1507803

Schematic diagram



Pin assignment of M12 male connector, 4-pos., B-coded, view of pin side

## Approvals

Approvals

---

Approvals

EAC / EAC

---

Ex Approvals


---

Approval details

## Termination resistor - SAC-5P-M12MS PB TR - 1507803

### Approvals

EAC		RU C- DE.AI30.B.01102
-----	---	--------------------------

EAC		EAC-Zulassung
-----	---	---------------

Phoenix Contact 2019 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>