

LINEAR TECHNOLOGY MATERIALS DECLARATION

ltc1663cs5#trmpbf

(Engineering Calculation)

TSOT-23

(printed on: 2020-07-11 18:34:29)

TOTAL MASS (g) : 0.012655

| COMPONENT MATERIAL | VENDOR/ INDUSTRY NAMES | CONSTITUENT NAME | CAS NUMBER | CONSTITUENT MASS (g) | CONSTITUENT (PPM) OF MATERIAL | CONSTITUENT (PPM) OF TOTAL PKG. | | |
|--------------------------------|----------------------------------|--------------------------------|------------|----------------------|-------------------------------|---------------------------------|----------------|----------------------|
| Active Device | Linear Technology | Silicon (Si) | 7440-21-3 | 0.000709 | 1000000 | 56024.2460938 | | |
| Die Coat | Dow Corning | Silicone | 69430-27-9 | 0.000000 | 0 | 0 | | |
| Lead Frame | Cu | Copper (Cu) | 7440-50-8 | 0.004485 | 975000 | 354398.78125 | | |
| | | Iron (Fe) | 7439-89-6 | 0.000110 | 24000 | 8692.0546875 | | |
| | | Phosphorus (P) | 7723-14-0 | 0.000001 | 300 | 79.0186843872 | | |
| | | Zinc (Zn) | 7440-66-6 | 0.000003 | 700 | 237.056060791 | | |
| | | Nickel (Ni) | 7440-02-0 | 0.000000 | 0 | 0 | | |
| | | Silicon (Si) | 7440-21-3 | 0.000000 | 0 | 0 | | |
| | | Magnesium (Mg) | 7439-95-4 | 0.000000 | 0 | 0 | | |
| | | Tin (Sn) | 7440-31-5 | 0.000000 | 0 | 0 | | |
| Lead Frame Total: | | | | 0.004599 | 1000000 | 363406.9375 | | |
| Plating | PMI | Exter. Plating Pb | 7439-92-1 | 0.000000 | 0 | 0 | | |
| | | Exter. Plating Sn | 7440-31-5 | 0.000635 | 1000000 | 50195.4882812 | | |
| | | External Plating Total: | | | | 0.000635 | 1000000 | 50195.4882812 |
| | | Inter. Plating Ni | 7440-02-0 | 0.000000 | 0 | 0 | | |
| | | Inter. Plating Ag | 7440-22-4 | 0.000080 | 1000000 | 6321.49462891 | | |
| Internal Plating Total: | | | | 0.000080 | 1000000 | 6321.49462891 | | |
| Die Attach | ELECTRICALLY CONDUCTIVE ADHESIVE | Silver (Ag) | 7440-22-4 | 0.000461 | 750000 | 36427.6132812 | | |
| | | Tin (Sn) | 7440-31-5 | 0.000000 | 0 | 0 | | |
| | | Lead (Pb) | 7439-92-1 | 0.000000 | 0 | 0 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.000000 | 0 | 0 | | |
| | | Indium (In) | 7440-74-6 | 0.000000 | 0 | 0 | | |
| | | Metal Oxide | | 0.000000 | 0 | 0 | | |
| | | Antimony (Sb) | 7440-36-0 | 0.000000 | 0 | 0 | | |
| | | Resin (EP) | | 0.000154 | 250000 | 12168.8769531 | | |
| Die Attach Total: | | | | 0.000615 | 1000000 | 48596.4921875 | | |
| Encapsulation | MULTI-AROMATIC RESIN Br/Sb FREE | Resin (EP) | | 0.000775 | 130000 | 61239.4804688 | | |
| | | Bromine (Br) | 40039-93-8 | 0.000000 | 0 | 0 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.004947 | 830000 | 390905.4375 | | |
| | | Antimony Trioxide (Sb2O3) | 1309-64-4 | 0.000000 | 0 | 0 | | |
| | | Metal Hydroxide | | 0.000209 | 35000 | 16514.9042969 | | |
| | | Carbon Black (C) | 1333-86-4 | 0.000030 | 5000 | 2370.56054688 | | |
| | | Encapsulation Total: | | | | 0.005961 | 1000000 | 471030.375 |
| Bond Wire Estimated | AFW/TANAKA/ Kn | Gold (Au) | 7440-57-5 | 0.000056 | 1000000 | 4425.04638672 | | |
| | | | | | TOTAL MASS (g) : | 0.012655 | | |