		۵	т	m	D		C
4 3	R 22.6 Max	N Thread		S			
			Keying Shown a	is example			
	CHARACTERISTICS		, , , 	Connector dimension	-		
	-Standard : Based on MIL-DTL-38999 Se	ries III		Dim Nominal			
2	-Shell Material: Stainless Steel-Shell Plating: Passivated-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elaston-Contact Plating: Gold over cop-Durability: 500 Mating cy-Delivered with Souriau contacts and Action	c ner per Alloy 0.8μm minimum rcles	- 	A 58.7±0.3 B 42.85+0.1/-0.15 R 32.5Max S 55.6±0.4 W 3+0.9/-0.1 VV THREAD M37x1-6g			SOURIAU shal due to a us the Specificatio (profes
	-Temperature Range : -65°C to +200						
	-Salt Spray : 500 hours						First Release
					IS Des	IS DATE	Latest modifica
						TITLE	
	BASIC SERIES: 8	D 7 - 25	К 43 S В			SCALE -	
<u> </u>	SHELL TYPE : Jam nut Receptacle					NA	$\neg \Psi$
	CONTACT TYPE : Standard Crimp Cont	tact				OURIAU	wwv
	SHELL SIZE : 25			CONTACT TYPE : SOCKET(5		ODMAT	
	PLATING : K = Passivated			CONTACT LAY	001.23-45	ORMAT A3	
	Н	G	F	E			С

 $\mathbf{\mathbf{n}}$

	Ξ		А		
					4
AYOUT SHOWN AS EXAMPLE					
all not be liable for any non-conformity or damage use of the Products which does not comply with ons issued by either of the Parties or by a third party essional recommendation, technical notice.) <u>Country</u> Jurisdiction & Control List FR Not Listed PN: 8D725K43SB					2
ation - by te:	Decente			MOD N°	
General linear Tolerances: ±	ACLE 8D SERIES NPRDS / PROJECT 859 This document is the property of			1	
W.SOURIAU.CO SOURIAU D 8D725K43		SOURIAU not be reproduc cated without pe			
	В		А		

Г	I G	П	т	
4	Contact Layout			Panel cutout JAM NUT RECEPTACLE (TYPE 7)
	$\begin{array}{ c c c c c } \hline (lnsert arrangement 25-43) \\ \hline \\ \hline Contact \\ position \\ ID \\ ID \\ ID \\ (mm) \\ (mm) \\ (mm) \\ A \\ + .069 (1.75) \\ + .531 (13.49) \\ C \\ + .324 (8.23) \\ + .425 (10.80) \\ E \\ + .424 (10.77) \\ + .531 (13.49) \\ C \\ + .531 (13.49) \\56 (5.21) \\56 (5.21) \\56 (5.21) \\51$			
ى	$\begin{array}{c c c c c c c c c c c c c c c c c c c $			Dim Nominal B 43.43+0/-0.25 ØC 44.7+0.25/-0
	Shell sizeArrangement no.Number of contactsSize 			SQUEIAU shall not be liable for any non-conformity or damage
				SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)
N				Country Jurisdiction & Control List FR Not Listed
				PN: 8D725K43SB A 04-10-2016 First Release
				ISS DATE Latest modification - by MOD N° Designed By: Date: CUSTOMER DRAWING
				TITLE Stainless Steel Receptacle 8D series
_				SCALE General linear NPRDS / PROJECT NA ± 859
				SOURIAU This document is the property of SOURIAU SOURIAU it must not be reproduced or it must not be reproduced or communicated without permission It must not be reproduced or
			I	FORMATSOURIAU DRG N°SHEETA38D725K43SB-C2/2
L	H G	F	E	D C B A