



- NOTES:
1. ALL DIMENSIONS IN MM
  2. GENERAL TOLERANCE: X.X =  $\pm 0.4$   
X.XX =  $\pm 0.25$
  3. TERM. NUMBERS FOR REFERENCE ONLY.
  4. CONTACT RATING: 0.2A @ 30VDC
  5. TRAVEL: 3.0 mm
  - ▲ 6. OPERATING FORCE:  $200 \pm 100$ gf
  7. LIFE EXPECTANCY: 10,000 CYCLES
  8. OPERATING TEMP:  $-20^{\circ}\text{C}$  to  $70^{\circ}\text{C}$
  9. ▲ DENOTES CRITICAL PARAMETER
  10. 2011/65/EU (ROHS) COMPLIANT



TITLE					EG1201 (SOLDER LUG, NON-SHORTING)				
SCALE	DATE	DR	DWG	REV					
2:1	2/19/2018	MW	P040010	B					

B	23226	Drawing updated and redrawn	2/19/18	MW
REV	PCR NO	DESCRIPTION	DATE	BY
<p style="font-size: small; text-align: center;">THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED</p>				