



## CHARACTERIS<sup>®</sup>

ω

 $\sim$ 

\_

	-Shell Material	: Composite			
	-Shell Plating	: Without Plating			
	-Insulator	: Thermoplastic			
	-Contacts	: Copper Alloy			
	-Seals & Grommet	: Silicon Elastomer			
	-Contact Plating	: Gold over copper Alloy $0.8 \mu m$ minimu			
	-Durability	: 500 Mating cycles			
-Delivered with Souriau contacts and Accessories					
	-Temperature Range	-65°C to +175°C			

Connector dimension				
Dim	Nominal			
Р	3.25±0.2			
РР	4.93±0.2			
R1	31.75			
R2	29.36			
S	39.7±0.3			
V	20.07+0/-1.25			
W	2.1/3.2			
Z	31.5 Max			
VV THREAD	M31x1-6g			

т <u></u>	п	m	l	J	0	σ	A		1
		S R1 R2 I I R2 I I R2 I I R2 I I R2 I I R2 I I R2 I I R2 I I I R2 I I I I			LAYOUT SH	OWN AS EXAMPLE			4
CHARACTERISTICS  -Standard : Based on MIL-DTL-38999 Series III Shell Material	Keying Show	Vn as example           Connector dimension           Dim         Nominal           P         3.25±0.2	-						
-Shell Material       : Composite         -Shell Plating       : Without Plating         -Insulator       : Thermoplastic         -Contacts       : Copper Alloy         -Seals & Grommet       : Silicon Elastomer		PP         4.93±0.2           R1         31.75           R2         29.36           S         39.7±0.3           V         20.07+0/-1.25			due to a use of the P the Specifications issued b	able for any non-conformity or roducts which does not comply by either of the Parties or by a t commendation, technical notice	with hird party .)		
-Contact Plating : Gold over copper Alloy 0.8μm minimun -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories	n	W         2.1/3.2           Z         31.5 Max           VV THREAD         M31x1-6g			PN: 8		n & Control List t Listed		2
-Temperature Range <sub>:</sub> -65°C to +175°C -Salt Spray : 2000 hours				A 30-09-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:	CU	STOMER DRAWING	MOD N°	
BASIC SERIES: 8D 0 - 21 SHELL TYPE : Square Flange Receptacle	X 72 S D			TITLE SCALE NA	Gene Tole	eral linear erances:	D series NPRDS / PROJECT 859		1
CONTACT TYPE : Standard Crimp Contact       ORIENTATION : D         SHELL SIZE : 21       CONTACT TYPE : SOCKET(500 Matings)						d or			
H G	F	E		A3		B	A	1/2	]

-	т	۵	н П	m	D	0
4	(	Contact Layout 72			2	Panel Cuto
		6#16				
ω	Ctc A B C D E F G H	X       Y         0       6.19         8.5       4.3         6.25       0         8.5       -4.3         0       -6.19         -8.5       -4.3         -6.25       0         -8.5       4.3				Dim ØA ØA R1 ØT
	L					
N						SOURIAU shall not be liable for an due to a use of the Products w the Specifications issued by either o (professional recommenda Count FR
						PN: 8D021
_						0-2016 First Release ATE Latest modification - by Date:
					TITLE	
_					SCALE NA	General linear Tolerances: ±
					SOURI	AU WWW.SOURIAU.
					FORMAT A3	SOURIAL 8D021X
	Н	G	F	E	D	С

