



Recommended PCB Layout
(Bottom View)

Material and Finish

Body: PBT Thermoplastic, Black
 Contacts: Copper Alloy
 Contact Plating: Gold Flash on Contacts, Tin on Terminations with Nickel under plated
 Shield: SPCC, Tin Plated

Electrical Characteristics

Contact Resistance:
 Before Test:
 Plug to Terminals: 30 Milliohms Max.
 After Test:
 Plug to Terminals: 60 Milliohms Max.
 Insulation Resistance:
 500 Megohms Min.
 Dielectric Withstanding Voltage:
 500V AC RMS For 1 Minute
 Current Rating:
 2 A at 12V DC

Mechanical Characteristics

Durability Test: 500 Cycles Min.
 Insertion Force: 0.4kg - 3.5kg
 Extraction Force: 0.5kg - 4.5kg
 Operating Temperature: -25°C to +80°C

Tolerances
X.X ± 0.3
X.XX ± 0.15
Unless Stated Otherwise



REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
B3	09/23/10	ECO #10-064	S. Vien	H. MA	R. Aguirre	8/02/05
B4	07/01/11	ECO #11-020	S. Vien	H. MA		
B5	01/15/13	ECO #12-063	S. Vien	P.DalCanto		
B6	02/17/15	ECO #15-017	H. MA	C. Furumasa	UNITS	mm
B7	05/28/15	ECO #14-021	C. Kelleher	H. Ma		
B8	04/25/19	ECO #19-040	G. Serrato	D. Shehan		

KMDGX-4S/4S-S4N

Stacked Mini-Din, 4/4, RoHS Compliant

Fully Shielded, Gold Contacts

