

## Specification Sheet

Part Number: 155-05400



1-Piece Cable Tie/Oval Stud Mount, Designed for 5.0 mm stud, 6.0" Long, PA66HS, Black, 500/pkg

<b>Article Number</b>	155-05400
<b>Type</b>	T50SOSSB5HEC
<b>Color</b>	Black (BK)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Oval mount design pushes on easy by hand without the need for tools.</li><li>• Design provides low insertion and high extraction force.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	The special oval shape provides for an approximate .20" (5.0 mm) lateral adjustment, allowing for any misalignment of the stud or incorrect positioning of the tie on the cables
<b>Short Description</b>	1-Piece Cable Tie/Oval Stud Mount, Designed for 5.0 mm stud, 6.0" Long, PA66HS, Black, 500/pkg

Global Part Name

T50SOSSB5HEC-PA66HS-BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

170

Length L (Imperial)

6.0

Length L (Metric)

160

Fixation Method

Weld Stud Fixing

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Outside Serrated

Width W (Imperial)

0.19

Width W (Metric)

4.6

Bundle Diameter Min (Imperial)

0.04

Bundle Diameter Min (Metric)

1.0

Bundle Diameter Max (Imperial)

1.4

Bundle Diameter Max (Metric)

35.0

Thickness T (Imperial)

0.05

<b>Thickness T (Metric)</b>	1.35
<b>Stud Length Max (Imperial)</b>	0.63
<b>Stud Length Max (Metric)</b>	16.0
<b>Stud Length Min (Metric)</b>	11.0
<b>Stud Diameter (Metric)</b>	5.0 mm
<b>Stud Diameter (Imperial)</b>	0.2
<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909988

**Content Unit(BMEcat)**

pcs.

**Weight (Metric)**

2.75