

## Specification Sheet

Part Number: 126-00044

All-in-one bundling and fastening solution reduces costs and assembly time.

The arrowhead design of these ties offers a low insertion force and a high extraction force.

High-spec materials and superior design deliver versatility, performance and value.



1-Pc Cable Tie/Arrowhead Mount, 6"L, 50lb, 0.04"–0.14" Panel Thickness, PA66, Natural, 1000/pkg

**Article Number** 126-00044

**Type** T50SSF

**Color** Natural (NA)

**Quantity Per** bag

**Product Description** One-piece mounting ties offer a complete solution by both bundling cable and simultaneously providing a mounting solution. The arrowhead design of this push mount inserts easily and locks securely in place. HellermannTyton's one-piece mounting ties combine high-specification materials with superior design to deliver dependable performance in a range of applications.

**Short Description** 1-Pc Cable Tie/Arrowhead Mount, 6"L, 50lb, 0.04"–0.14" Panel Thickness, PA66, Natural, 1000/pkg

**Global Part Name** T50SSF-PA66-NA

**Minimum Tensile Strength (Imperial)** 50.0

**Minimum Tensile Strength (Metric)** 225.0

**Length L (Imperial)** 6.25

**Length L (Metric)** 159.0

**Fixation Method** Arrowhead

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.19

**Width W (Metric)** 4.7

**Bundle Diameter Min (Imperial)** 0.06

**Bundle Diameter Min (Metric)** 1.5

**Bundle Diameter Max (Imperial)** 1.38

**Bundle Diameter Max (Metric)** 35.0

<b>Height H (Imperial)</b>	.30
<b>Height H (Metric)</b>	7.50
<b>Panel Thickness Min (Imperial)</b>	0.039
<b>Panel Thickness Max (Imperial)</b>	0.14
<b>Panel Thickness Min (Metric)</b>	1.0
<b>Panel Thickness Max (Metric)</b>	3.56
<b>Mounting Hole Diameter D (Imperial)</b>	0.25 " - 0.28
<b>Mounting Hole Diameter D (Metric)</b>	6.4 - 7.1 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.25
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.28
<b>Mounting Hole Diameter D Max (Metric)</b>	7.1
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)

**ROHS Compliant** Yes

**UL Recognized (US)** Yes

**UL Recognized (US and Canada)** Yes

**Package Quantity (Imperial)** 1000

**Package Quantity (Metric)** 1000

**Customs Number** 3926909988