

Industrial Ethernet VDATA CAT6

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



- Suitable for Cat. 5 (up to 100 MHz) and Cat. 6 (up to 250 MHz Class E)
- Suitable for PoE (acc. to IEEE 802.3af) and PoE+ (acc. to IEEE 802.3at)
- Protection of all wire pairs
- Connection via RJ45 sockets
- Metal housing

General ordering data

Type	VDATA CAT6
Order No.	1348590000
Version	Terminal rail fixing, Surge protection, 48 V, 1 A, According to IEC61643-21
GTIN (EAN)	4050118153002
Qty.	1 pc(s).

**Industrial Ethernet
VDATA CAT6**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Dimensions and weights**

Width	19 mm	Width (inches)	0.748 inch
Height	75 mm	Height (inches)	2.953 inch
Depth	46 mm	Depth (inches)	1.811 inch
Net weight	139 g		

Temperatures

Humidity	0...95 % (no condensation)	Operating temperature, max.	80 °C
Operating temperature, min.	-40 °C	Storage temperature, max.	85 °C
Storage temperature, min.	-40 °C	Operating temperature	-40 °C...80 °C
Storage temperature	-40 °C...85 °C		

General data

Colour	Silver grey	Design	Miscellaneous, Adapter plug
Mounting rail	TS 35 x 15, TS 35 x 7.5	Protection degree	IP20
Segment	Data surge protection	Suitable for	RJ45 plug
Version	Cat.6		

Insulation coordination acc. to EN 50178

Pollution severity	2	Surge voltage category	III
--------------------	---	------------------------	-----

Rated data IEC / EN

Discharge current I_{max} (8/20 μ s) wire-PE	10 kA	Discharge current I_n (8/20 μ s) wire-PE	5 kA
Discharge current, I_{imp} (10/350 μ s)	1 kA	Frequency range, max.	250 MHz
Insertion loss	≤ 1 dB @ 250 MHz	Lightning test current, I_{imp} (10/350 μ s) Wire-PE	1 kA
Max. continuous voltage, U_c (DC)	50 V	Protection level U_p (typ.)	≤ 550 V
Rated current I_N	1 A	Rated voltage (DC)	48 V
Requirements category acc. to IEC 61643-21	C2, D1	Response time	< 1 ns
Signal transmission properties (-3 dB)	250 kHz	Standards	According to IEC61643-21
Suitable for	RJ45 plug	Surge current-carrying capacity C2	10 kA
Surge current-carrying capacity D1	1 kA 10/350 μ s	Voltage type	AC/DC
Volume resistance	$< 0.1 \Omega$	Wire-PE capacitance @ 1 MHz, 1 Vrms	20 pF
Wire-wire capacitance @ 1 MHz, 1 Vrms	30 pF		

Connection data

Wire connection method	RJ45-Port
------------------------	-----------

Rated data UL

Voltage Breakdown (VDC) L-G	72 V - 120 V	Voltage Breakdown (VDC) L-L	53 V - 73 V
Voltage type	DC	Certificate No. (UL)	E311081
Rated Voltage U_N	48 V		

Data sheet

**Industrial Ethernet
VDATA CAT6**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Classifications

ETIM 3.0	EC001473	ETIM 5.0	EC000510
ETIM 6.0	EC000943	UNSPSC	30-21-19-21
eClass 5.1	27-13-08-01	eClass 6.2	27-13-08-02
eClass 7.1	27-14-02-01	eClass 8.1	27-14-02-01
eClass 9.0	27-14-02-01	eClass 9.1	27-13-08-07

Product information

Product information	UL File e311081
Descriptive text technical data	Can also be used for CAT.5 applications

Approvals

Approvals




ROHS	Conform
------	---------

Downloads

Approval/Certificate/Document of Conformity	CE PAPER
Brochure/Catalogue	CAT 4.4 ELECTR 16/17 EN CAT 9 IETH 15/16 EN
Engineering Data	EPLAN, WSCAD
Engineering Data	STEP
User Documentation	Instruction sheet

**Industrial Ethernet
VDATA CAT6**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Circuit diagram