



- Notes:**
- Material and Finish:
 - Coupler Ring: Zinc Die-Cast, Nickel Plated
 - Plug Housing: Zinc Die-Cast, Nickel Plated
 - Cable Gland: Brass, Nickel Plated
 - Cable Gland Rubber Ring: NBR, Color: Black
 - Cable Fitting: PA (Black), UL94 V-0
 - Interfacial Seal: Silicon, Color: White
 - Plug Protective Cap: Polyester (Black); UL94 V-0
 - Tether: Polycarbonate (Black)

- Duplex LC Connector
- Housing: PEI, UL94 V-0, Color: **SM Blue/MM Beige/APC SM Green**
 - Inner Sub Assembly: Zirconia, Metal and PTFE
 - Crimp Barrel: Brass, Nickel Plated
 - Ferrule: Brass, Nickel Plated
 - Dust Cap: PC, Color: White
 - Duplex LC Clip: PC, Color: Black
 - Operating Temperature: -40°C to +85°C

- IP67 rated when covered or fully mated with the appropriate mating connector
- Accepts 4.5mm to 8.0mm outside diameter fiber optic cable

Directive 2002/95/EC RoHS Compliant

Description	Part Number
Nickel Plated Die-Cast Duplex LC Single Mode Plug Kit + Plastic Plug Cover Assembly	17-300730
Nickel Plated Die-Cast Duplex LC Multi Mode Plug Kit + Plastic Plug Cover Assembly	17-300740
Nickel Plated Die-Cast Duplex LC APC Single Mode Plug Kit + Plastic Plug Cover Assembly	17-300750

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY MANNER AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION.	Customer:		Tolerance Unless otherwise specified			Scale: NTS	Dim. in mm	
	Name	Title	Approval Date	0 PLC ±0.30 1 PLC ±0.20 2 PLC ±0.10 3 PLC ±0.05 ANGLES ±1°		Autodesk Inventor	Material: See Notes	
				2012	Date	Name	Title: IP67 Industrial Duplex LC Plug + Protective Cap Assembly Kit Nickel Plated Die-Cast Version	
				Draw.	Apr. 26	Vincent Ke		
			Appd.	Apr. 26	J. Chaudry			
						Drawing No.: 17K1A328		
						Part No.: SEE P/N ABOVE		
						DIN A3		
						Sheet 1/1		

