




Contact Layout



| Contacts<br>(Insert arrangement 21-16) |             |             |                     |             |             |
|--|-------------|-------------|---------------------|-------------|-------------|
| Contact position ID                    | Location    |             | Contact position ID | Location    |             |
|  | X-axis      | Y-axis      |                     | X-axis      | Y-axis      |
| A                                      | +118 (3.00) | +322 (8.18) | J                   | -341 (8.66) | +036 (0.91) |
| B                                      | +271 (6.88) | +211 (5.36) | K                   | -271 (6.88) | +211 (5.36) |
| C                                      | +341 (8.66) | +036 (0.91) | L                   | -118 (3.00) | +322 (8.18) |
| D                                      | +308 (7.82) | -150 (3.81) | M                   | +000 (0.00) | +175 (4.45) |
| E                                      | +182 (4.62) | -290 (7.37) | N                   | +154 (3.91) | +062 (1.57) |
| F                                      | +000 (0.00) | -343 (8.71) | P                   | +094 (2.39) | -122 (3.10) |
| G                                      | -182 (4.62) | -290 (7.37) | R                   | -094 (2.39) | -122 (3.10) |
| H                                      | -308 (7.82) | -150 (3.81) | S                   | -154 (3.91) | +062 (1.57) |

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|------------------|------------|
| 21         | -16             | 16                 | 16            | II             | All              | MS20055-16 |

Panel Cutout



| Dim | Nominal    |
|-----|------------|
| ØA  | 36.12 min  |
| ØAA | 32.16 min  |
| R1  | 31.75      |
| ØT  | 3.25 ±0.13 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

PN: 8D021F16AB

|                |                                    |                            |   |
|----------------|------------------------------------|----------------------------|---|
| A              | 02-11-2016                         | First Release              |   |
| ISS            | DATE                               | Latest modification - by   | MOD N°  |
| Designed By:   |                                    | Date:                      | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | Aluminium Receptacle 8D series     |                            |   |
| SCALE          |                                    | General linear Tolerances: | NPRDS / PROJECT   |
| NA             |                                    | ±--                        | <b>859</b>  |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>             |                            | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>SOURIAU DRG N° 8D021F16AB-C</b> |                            | SHEET 2/2   |