

## A50PT41002660K

Aliases (50PT41002660K)

A50, Film, Metallized Polyester, Automotive Grade, 1 uF, 10%, 220 VAC, 630 VDC, 85°C

### FRONT VIEW



### SIDE VIEW



Click [here](#) for the 3D model.

#### Dimensions

D	17.5mm MAX
L	33mm MAX
LL	20mm MIN
F	1mm +/-0.05mm

#### Packaging Specifications

Packaging	T&R
Packaging Quantity	200

#### General Information

Series	A50
Dielectric	Metallized Polyester
Style	Axial
Features	Automotive Grade
RoHS	Yes
Lead	Wire Leads
Qualifications	AEC-Q200
AEC-Q200	Yes
Component Weight	9 g
Miscellaneous	Above 85C DC And AC Voltage Derating Is 1.25%/C. maxK0 = 7500.

#### Specifications

Capacitance	1 uF
Capacitance Tolerance	10%
Voltage AC	220 VAC
Voltage DC	630 VDC, 472.5 VDC (105C)
Temperature Range	-55/+105°C
Rated Temperature	85°C
Dissipation Factor	0.8% 1kHz, 1.2% 10kHz
Insulation Resistance	10 GOhms
Max dV/dt	6 V/us
Inductance	7 nH