



注記 NOTES

- 材料 MATERIAL
ハウジング : ガラス入り耐熱樹脂、白色、UL94V-0
HOUSING : G.F.HEAT RESISTANT PLASTIC,WHITE, UL94V-0
ターミナル : リン青銅
TERMINAL : PHOSPHOR BRONZE
- ターミナルめっき仕様 TERMINAL PLATING
接点部 : 金めっき (表参照)
CONTACT AREA : GOLD/SEE TABLE
プレスフィット部 : PURE-TIN 1.0~2.5 μ m.
PRESS-FIT AREA : PURE-TIN 1.0-2.5 μ m.
下地めっき : ニッケルめっき 2.0 μ mMIN.
UNDER-PLATING : NICKEL 2.0 μ mMIN.
- 推奨基板厚 : 1.6 mm.
RECOMMENDED P.C.B.THICKNESS

94	95.98	0.76 μ m MIN.	54753-1929	192
		0.38 μ m MIN.	54753-1928	
46	47.98	0.76 μ m MIN.	54753-0969	96
		0.38 μ m MIN.	54753-0968	
22	23.98	0.76 μ m MIN.	54753-0489	48
		0.38 μ m MIN.	54753-0488	
10	11.98	0.76 μ m MIN.	54753-0249	24
		0.38 μ m MIN.	54753-0248	
B	A	Au PLATING THICKNESS 金めっき厚	MATERIAL NO. 製品番号	CKT. 極数
54753-****				
MODEL NO.				

3. 基板穴推奨寸法 (部品実装側)
RECOMMENDED P.C.B. LAYOUT (MOUNTING SIDE)

NEW RELEASE EONNO. DRWN: DAVID HU 05/03/14 CHK: HARVEY 05/03/14 APPR:	REV DESCRIPTION	MATERIAL 材料 注記参照 SEE NOTES	GENERAL TOLERANCES: (UNLESS SPECIFIED) 一般公差	SCALE 2-1 <input checked="" type="checkbox"/> mm <input type="checkbox"/> INCH	DESIGN UNITS <input checked="" type="checkbox"/> mm <input type="checkbox"/> INCH	THIRD ANGLE PROJECTION <input checked="" type="checkbox"/> THIRD ANGLE <input type="checkbox"/> FIRST ANGLE	DIMENSIONS: <input type="checkbox"/> mm <input type="checkbox"/> INCH <input type="checkbox"/> mm <input checked="" type="checkbox"/> mm ONLY		SHT	REV		
		FINISH 仕上げ 注記参照 SEE NOTES	10 UNDER 未満 ± 0.2	DRAWN BY & DATE DAVID HU 05/03/14	TITLE: "MFB" B/B CONN. (FB+) STRAIGHT REC. ASS'Y 4ROWS DIP TYPE (SOLDER TAIL=3.3mm) (LEAD-FREE)							
		WIRE RANGE 適用電線範囲	10 OVER 以上 30 UNDER 未満 ± 0.25	CHECKED BY & DATE HARVEY 05/03/14	APPROVED BY & DATE VINCENT 05/03/14				MOLEX INCORPORATED			
		INS. RANGE 被覆外径	30 OVER 以上 ± 0.3	CAD FILENAME	MATERIAL NO. ---	DRAWING NO. SD-54753-001	SHEET NO. 1 OF 1		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.		SIZE B	

DO NOT SCALE DRAWING