

6 5 4 3 2 1

APPROVED: _____
 DATE: _____ TITLE: _____

| | | | | |
|-----|-------|-------------|--------|------|
| Rev | AWO # | Description | Date | Appr |
| - | | RELEASED | 9/4/20 | |

SECTION A-A
SCALE 1:1

| | | |
|--------------|-------------------------|----------------------|
| OPSA1ANNC2P2 | SC/APC W/Panel Ground | 7737C Green |
| OPSB1ANNC2P2 | SC/PC W/Panel Ground | 2184C Blue |
| OPSA1ANNC2N2 | SC/APC W/O Panel Ground | 7737C Green |
| OPSB1ANNC2N2 | SC/PC W/O Panel Ground | 2184C Blue |
| PART NUMBER | DESCRIPTION | Housing&Insert color |

SPECIFICATIONS:

Material:
 Housing: Plastic, rated UL 94V-0, Color: See Chart
 Sleeve: Zirconia ceramic
 Electrical:
 Standards of IEC, EIA/TIA, Telcordia
 Repeatability: 500 cycles
 Insertion loss: 0.2dB max
 Temperature Rating:
 Operating temperature: -25°C to +70°C
 Environmental:
 Lead free, RoHS compliant.

UNLESS OTHERWISE SPECIFIED
 ALL DIMENSIONS ARE MILLIMETERS
 TOLERANCES: EXCEPT AS NOTED
 MM ANGLE
 .X ± 0.35 .X* ± 2°
 .XX ± 0.30 .XX* ± 1°
 .XX ± 0.25 .XX* ± 1°
 .XXX ± 0.15 .XXX* ± 0.5°

ADAM TECH INTERCONNECTS
 909 Rahway Avenue,
 Union, NJ 07083
 Phone: 908-687-5000
 Fax: 908-687-5710

| | | |
|-----------|----|--------|
| APPROVALS | | DATE |
| DRAWN | OW | 9/4/20 |
| CHECKED | JL | 9/4/20 |
| APPROVED | | |

| | | |
|--|--------------|-------------------------|
| TITLE | | |
| SC TYPE ADAPTER, APC & PC, 1 PORTS LONG-EARED, WITH SC CUCURBIT TYPE DUST CAP | | |
| SIZE | PART NO. | REV. |
| X | OPSX1ANNC2X2 | - |
| REF: | S00005C | SCALE: NTS SHEET 1 OF 2 |

6 5 4 3 2 1

6 5 4 3 2 1

APPROVED: _____
 DATE: _____ TITLE: _____

| Rev | AWO # | Description | Date | Appr |
|-----|-------|-------------|--------|------|
| - | | RELEASED | 9/4/20 | |

SECTION A-A
SCALE 1:1

| | | |
|--------------|-------------------------|----------------------|
| OPSA1ANNC2P2 | SC/APC W/Panel Ground | 7737C Green |
| OPSB1ANNC2P2 | SC/PC W/Panel Ground | 2184C Blue |
| OPSA1ANNC2N2 | SC/APC W/O Panel Ground | 7737C Green |
| OPSB1ANNC2N2 | SC/PC W/O Panel Ground | 2184C Blue |
| PART NUMBER | DESCRIPTION | Housing&Insert color |

SPECIFICATIONS:

Material:
 Housing: Plastic, rated UL 94V-0, Color: See Chart
 Sleeve: Zirconia ceramic
 Electrical:
 Standards of IEC, EIA/TIA, Telcordia
 Repeatability: 500 cycles
 Insertion loss: 0.2dB max
 Temperature Rating:
 Operating temperature: -25°C to +70°C
 Environmental:
 Lead free, RoHS compliant.

UNLESS OTHERWISE SPECIFIED
 ALL DIMENSIONS ARE MILLIMETERS
 TOLERANCES: EXCEPT AS NOTED
 MM ANGLE
 .X ± 0.35 .X* ± 2°
 .XX ± 0.30 .XX* ± 1°
 .XX ± 0.25 .XX* ± 1°
 .XXX ± 0.15 .XXX* ± 0.5°

ADAM TECH INTERCONNECTS
 909 Rahway Avenue,
 Union, NJ 07083
 Phone: 908-687-5000
 Fax: 908-687-5710

| APPROVALS | | DATE |
|-----------|----|--------|
| DRAWN | OW | 9/4/20 |
| CHECKED | JL | 9/4/20 |
| APPROVED | | |

| | | |
|--|--------------|--------------|
| TITLE | | |
| SC TYPE ADAPTER, APC & PC, 1 PORTS LONG-EARED, WITH SC CUCURBIT TYPE DUST CAP | | |
| SIZE | PART NO. | REV. |
| X | OPSX1ANNC2X2 | - |
| REF: S00005C | SCALE: NTS | SHEET 1 OF 2 |

6 5 4 3 2 1