



TECHNICAL

AGENCY APPROVAL:	cULus
RATED SUPPLY VOLTAGE:	120VAC
RATED CURRENT:	15A
RESET TYPE:	MANUAL
OPERATING FREQUENCY:	60 Hz
TYPE:	CLASS A
GROUND TRIP CURRENT:	4-6 mA
OVERLOAD CURRENT:	90 AMP
INSULATION VOLTAGE:	1,500 VRMS - 1 MINUTE
ENDURANCE OPERATIONS:	3000 OPERATIONS
ENCLOSURE:	NEMA 3R

MATERIAL NUMBER	ENGINEERING NUMBER	LENGTH "A"	LENGTH "L"
1301530054	15052-1	9.50 IN.	1 FT 11.4 IN.
1301530067	15052-6	4 FT. 10.50 IN.	6 FT. 0.4 IN.
1301530060	15052-25	23 FT. 10.50 IN.	25 FT. 0.4 IN.
1301530064	15052-50	48 FT. 10.50 IN.	50 FT. 0.4 IN.
1301530055	15052-100	98 FT. 10.50 IN.	100 FT. 0.4 IN.

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION									
FUNCTIONAL SYMBOLS E=0 E=0 E=0	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	SCALE	CURRENT REV DESC: UPDATED TABLE AND ADDED TECHNICAL						
	DIMENSION UNITS	INCH NTS							
	GENERAL TOLERANCES (UNLESS SPECIFIED)								
DIVISIONAL SYMBOLS	ANGULAR TOL	± °							
	4 PLACES	±							
	3 PLACES	±							
	2 PLACES	±							
	1 PLACE	±							
0 PLACES	±								
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER	SHEET NUMBER		
			B-SIZE	130153	SEE TABLE	GENERAL MARKET	1 OF 1		

molex

GFCI IN-LINE 15A W/WATERTITE PLUG & CONNECTOR

PRODUCT CUSTOMER DRAWING

DOCUMENT NUMBER: 1301530067
DOC TYPE: PSD
DOC PART: 000
REVISION: B