

SAC-6P-DTMS-5P-M12FS P - Adapter



1088173

<https://www.phoenixcontact.com/us/products/1088173>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Adapter, 5-position, Plug straight DEUTSCH DT04-6P, on Socket straight M12, coding: A



Commercial Data

Item number	1088173
Packing unit	1 pc
Sales Key	BF13
Product Key	BF1GGA
GTIN	4055626887739
Weight per Piece (including packing)	14.15 g
Weight per Piece (excluding packing)	14.15 g
Customs tariff number	85444290
Country of origin	CN

SAC-6P-DTMS-5P-M12FS P - Adapter



1088173

<https://www.phoenixcontact.com/us/products/1088173>

Technical Data

Notes

General	Sufficient strain relief at the connection point can prevent premature stress and wear. Utilize tie down accessories to eliminate bending and dynamic loads on the connector.
---------	---

Product properties

Product type	M8/M12 adapters
Number of positions	5
Coding	A

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Electrical properties

Nominal voltage U_N	48 V AC
	60 V DC
Nominal current I_N	4 A

Material specifications

Flammability rating according to UL 94	V0
Seal material	Viton
Material of grip body	GF nylon
Contact material	CuSn
Contact surface material	Ni/Au M12, Ni/Sn DT
Contact carrier material	GF nylon
Material for screw connection	Plastic

Connector

Connection 2

Coding type	A
-------------	---

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 100
-----------------------------	------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67
	IP69K
Ambient temperature (operation)	-40 °C ... 105 °C

SAC-6P-DTMS-5P-M12FS P - Adapter



1088173

<https://www.phoenixcontact.com/us/products/1088173>

Standards and regulations

Standards/specifications	IEC 61076-2-101
Standards/specifications	SAE J2030

SAC-6P-DTMS-5P-M12FS P - Adapter

1088173


<https://www.phoenixcontact.com/us/products/1088173>

Drawings

Circuit diagram



Dimensional drawing



DT/M12 adapter


SAC-6P-DTMS-5P-M12FS P - Adapter

1088173

<https://www.phoenixcontact.com/us/products/1088173>




Schematic diagram



DEUTSCH DT04-5P pin assignment

Schematic diagram



Pin assignment M12 socket, 5-pos., A-coded, view female side

SAC-6P-DTMS-5P-M12FS P - Adapter



1088173

<https://www.phoenixcontact.com/us/products/1088173>

Classifications

ECLASS

ECLASS-11.0	27440106
ECLASS-12.0	27440106
ECLASS-13.0	27440106

ETIM

ETIM 8.0	EC002925
----------	----------

UNSPSC

UNSPSC 21.0	31251500
-------------	----------

SAC-6P-DTMS-5P-M12FS P - Adapter



1088173

<https://www.phoenixcontact.com/us/products/1088173>

Environmental Product Compliance

REACH SVHC

Lead 7439-92-1

SAC-6P-DTMS-5P-M12FS P - Adapter

1088173

<https://www.phoenixcontact.com/us/products/1088173>



Accessories

WT-HF 3,6X140 BK - Cable tie

3240745

<https://www.phoenixcontact.com/us/products/3240745>



Cable binders for quick and secure bundling, standard version

WT-BASE LS HF 4 BK - Cable binder base

3240707

<https://www.phoenixcontact.com/us/products/3240707>



Cable binder base, for cable binders up to 4 mm wide, self-adhesive (rubber) and screwable, 4 mm fixing hole, 4-sided cable binder feed-through

SAC-6P-DTMS-5P-M12FS P - Adapter



1088173

<https://www.phoenixcontact.com/us/products/1088173>

EML-HA (15X9)R - Label for rough surfaces

0830600

<https://www.phoenixcontact.com/us/products/0830600>



Label for rough surfaces, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: adhesive, lettering field size: 15 x 9 mm, Number of individual labels: 2500

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com