



CONNECTOR SPECIFICATION:

VOLTAGE RATING	600V AC/DC
AMPERAGE RATING	2P: 18 AMPS, 3P: 18 AMPS, 4P: 15 AMPS
PROTECTION	IP67
OPERATING TEMP.	-20°C TO 105°C
UL CERTIFICATIONS	UL RECOGNIZED, FILE NO. E46237

POLES	MATERIAL NO.	ENGINEERING NO.	FINISHED LENGTH
4	1300000074	32638	6.0 FT. +2.19"-0 [183CM+56mm-0]
4	1300000076	32639	12.0 FT. +3.50"-0 [366 CM +89mm-0]

ITEM	COMPONENT	MATERIAL	FINISH
5	LABEL	VINYL	YELLOW
4	COUPLING	THERMOPLASTIC	BLACK
3	CONTACT SOCKET	COPPER ALLOY	UN-PLATED
2	OVERMOLD	RUBBER	YELLOW
1	CABLE-14 AWG SOW	CPE JACKET	YELLOW

RELEASED EC NO: IPG2013-0663 DRWN: RSTONE 2012/11/20 CHKD: K JOZWIK APPR: JFMURPHY 2013/02/07	DESCRIPTION REV	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED) mm INCH 4 PLACES ±--- ±--- 3 PLACES ±--- ±--- 2 PLACES ±--- ±.01 1 PLACE ±0.3 ±--- ANGULAR ±2°	DIMENSION STYLE INCH/MM DRAWN BY: RSTONE DATE: 2012/11/20 CHECKED BY: K JOZWIK DATE: 2012/11/28 APPROVED BY: JFMURPHY DATE: 2013/02/07	SCALE: --- DESIGN UNITS: INCH THIRD ANGLE PROJECTION	TITLE: QUICK CHANGE CABLE ASSY 2-4P FEMALE, 14 AWG
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	MATERIAL NO.: SEE CHART	MOLEX INCORPORATED	DOCUMENT NO.: SD-130000-004	SHEET NO.: 1 OF 1
		SIZE B	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			