


## A70MT4100AA00K

Aliases (70MT4100AA00K)

A70, Film, Metallized Polypropylene, General Purpose, 1 uF, 10%, 220 VAC, 400 VDC, 85°C



Click [here](#) for the 3D model.

| Dimensions |               |
|------------|---------------|
| D          | 16.5mm MAX    |
| L          | 33mm MAX      |
| LL         | 38mm MIN      |
| F          | 1mm +/-0.05mm |

| Packaging Specifications |           |
|--------------------------|-----------|
| Packaging                | Bulk, Bag |
| Packaging Quantity       | 200       |

| General Information |  |
|---------------------|--|
| Series              | A70  |
| Dielectric          | Metallized Polypropylene                                       |
| Style               | Axial  |
| RoHS                | Yes  |
| Lead                | Wire Leads   |
| AEC-Q200            | No   |
| Component Weight    | 5.6 g  |
| Miscellaneous       | Above 85C DC And AC Voltage Derating Is 1.25%/C. maxKO = 3200. |

| Specifications        |                         |
|-----------------------|-------------------------|
| Capacitance           | 1 uF                    |
| Capacitance Tolerance | 10%                     |
| Voltage AC            | 220 VAC                 |
| Voltage DC            | 400 VDC, 300 VDC (105C) |
| Temperature Range     | -55/+105°C              |
| Rated Temperature     | 85°C                    |
| Dissipation Factor    | 0.06% 1kHz, 0.1% 10kHz  |
| Insulation Resistance | 30 GOhms                |
| Max dV/dt             | 4 V/us                  |
| Inductance            | 33 nH                   |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.