



Specification

- Lever body
Zinc die-cast
- Powder coated
 - Black, RAL 9005, textured finish
 - **SW**
- Orange, RAL 2004, textured finish
- **OS**
- Red, RAL 3000, textured finish
- **RS**
- Silver, RAL 9006, textured finish
- **SR**
- Chrome-plated finish
- **CR**
- Uncoated, tumbled finish
- **RH**
- Threaded stud / retaining screw
Steel
 - Blackened finish
 - Tensile strength class 5.8
- **RoHS compliant**



Information

GN 300 adjustable levers have proven to be ideal wherever parts have to be clamped in a confined space or in a particular lever position. The insert is connected to the lever via serrations that can easily be disengaged.

Pulling the lever upwards disengages the serrations, allowing it to be swiveled to the ideal clamping position. When releasing the lever, the serrations automatically re-engage.

see also...

- Adjustable Levers GN 300.1 (with Stainless Steel Threaded Stud)
- Adjustable Levers GN 300.5 (Stainless Steel, Matte Shot-Blasted Finish)
- Straight Adjustable Levers GN 302
- Adjustable Levers GN 300.4 (with Secure Clamping Force)
- Adjustable Levers GN 303 (with Push Button)

On request

- Black, RAL 9011, silk shiny finish
- **SZ**
- Special colors, stud lengths, and threads

How to order (Inch)	1 Lever length l_1
1 2 3 4	2 Thread d_1
GN 300-78-1/2X13-32-RH	3 Thread length l_2
	4 Finish (Color)

How to order (Metric)	1 Lever length l_1
1 2 3 4	2 Thread d_1
GN 300-63-M8-25-SW	3 Thread length l_2
	4 Color (Finish)

Inch table

Dimensions in: inches - millimeters

1 l ₁	2 d ₁ Thread	3 l ₂									d ₃	d ₄	h ₁	h ₂	h ₃	h ₄ Stroke
1.18 30	10 x 32	.39 10	.47 12	.63 16	-	-	-	-	-	-	.39 10	.51 13	.96 24.5	.16 4	1.22 31	.14 3.5
1.18 30	10 x 24	.47 12	.63 16	.79 20	.98 25	1.26 32	-	-	-	-	.39 10	.51 13	.96 24.5	.16 4	1.22 31	.14 3.5
1.18 30	1/4 x 20	.39 10	.47 12	.63 16	.79 20	.98 25	1.26 32	1.57 40	1.77 45	-	.39 10	.51 13	.96 24.5	.16 4	1.22 31	.14 3.5
1.77 45	10 x 32	.39 10	.47 12	.63 16	.79 20	.98 25	1.26 32	-	-	-	.39 10	.51 13	.96 24.5	.16 4	1.34 34	.14 3.5
1.77 45	10 x 24	.47 12	.63 16	.79 20	.98 25	1.26 32	-	-	-	-	.39 10	.51 13	.96 24.5	.16 4	1.34 34	.14 3.5
1.77 45	1/4 x 20	.39 10	.47 12	.63 16	.79 20	.98 25	1.26 32	1.57 40	1.77 45	-	.39 10	.51 13	.96 24.5	.16 4	1.34 34	.14 3.5
2.48 63	1/4 x 20	.47 12	.63 16	.79 20	.98 25	-	-	-	-	-	.53 13.5	.69 17.5	1.22 31	.26 6.5	1.77 45	.16 4
2.48 63	5/16 x 18	.47 12	.63 16	.79 20	.98 25	1.26 32	1.57 40	1.77 45	1.97 50	2.48 63	.53 13.5	.69 17.5	1.22 31	.26 6.5	1.77 45	.16 4
2.48 63	3/8 x 16	.63 16	.79 20	.98 25	1.26 32	1.57 40	1.77 45	1.97 50	2.48 63	-	.53 13.5	.69 17.5	1.22 31	.26 6.5	1.77 45	.16 4
3.07 78	3/8 x 16	.63 16	.79 20	.98 25	1.26 32	1.57 40	1.77 45	1.97 50	2.48 63	-	.63 16	.83 21	1.42 36	.31 8	2.13 54	.16 4
3.07 78	1/2 x 13	.63 16	.79 20	.98 25	1.26 32	1.57 40	1.77 45	1.97 50	-	-	.63 16	.83 21	1.42 36	.31 8	2.13 54	.16 4
3.62 92	3/8 x 16	.63 16	.79 20	.98 25	1.26 32	1.57 40	1.77 45	1.97 50	2.48 63	-	.75 19	.94 24	1.69 43	.43 11	2.52 64	.16 4
3.62 92	1/2 x 13	.63 16	.79 20	.98 25	1.26 32	1.38 35	1.57 40	1.77 45	1.97 50	2.48 63	.75 19	.94 24	1.69 43	.43 11	2.52 64	.16 4
4.25 108	1/2 x 13	.98 25	1.26 32	1.57 40	1.97 50	2.17 55	2.48 63	-	-	-	.91 23	1.18 30	1.99 50.5	.47 12	2.95 75	.20 5
4.25 108	5/8 x 11	1.26 32	1.57 40	1.97 50	2.17 55	2.48 63	-	-	-	-	.91 23	1.18 30	1.99 50.5	.47 12	2.95 75	.20 5

Metric table

Dimensions in: millimeters - inches

1 l ₁	2 d ₁ Thread	3 l ₂									d ₃	d ₄	h ₁	h ₂	h ₃	h ₄ Stroke
30 1.18	M 3	-	6 .24	8 .31	10 .39	12 .47	16 .63	-	-	-	10 .39	13 .51	24.5 .96	4 .16	31 1.22	3.5 .14
30 1.18	M 4	-	12 .47	16 .63	20 .79	25 .98	32 1.26	-	-	-	10 .39	13 .51	24.5 .96	4 .16	31 1.22	3.5 .14
30 1.18	M 5	M 6	12 .47	16 .63	20 .79	25 .98	32 1.26	40 1.57	50 1.97	-	10 .39	13 .51	24.5 .96	4 .16	31 1.22	3.5 .14
45 1.77	M 4	-	12 .47	16 .63	20 .79	25 .98	32 1.26	-	-	-	10 .39	13 .51	24.5 .96	4 .16	34 1.34	3.5 .14
45 1.77	M 5	M 6	12 .47	16 .63	20 .79	25 .98	32 1.26	40 1.57	50 1.97	-	10 .39	13 .51	24.5 .96	4 .16	34 1.34	3.5 .14
63 2.48	M 6	M 8	12 .47	16 .63	20 .79	25 .98	32 1.26	40 1.57	50 1.97	63 2.48	13.5 .53	17.5 .69	31 1.22	6.5 .26	45 1.77	4 .16
63 2.48	M 10	-	20 .79	25 .98	32 1.26	40 1.57	50 1.97	63 2.48	80 3.15	-	13.5 .53	17.5 .69	31 1.22	6.5 .26	45 1.77	4 .16
78 3.07	M 8	M 10	16 .63	20 .79	25 .98	32 1.26	40 1.57	50 1.97	63 2.48	80 3.15	16 .63	21 .83	36 1.42	8 .31	54 2.13	4 .16
78 3.07	M 12	-	20 .79	25 .98	32 1.26	40 1.57	50 1.97	63 2.48	80 3.15	-	16 .63	21 .83	36 1.42	8 .31	54 2.13	4 .16
92 3.62	M 10	M 12	16 .63	20 .79	25 .98	32 1.26	40 1.57	50 1.97	63 2.48	80 3.15	19 .75	24 .94	43 1.69	11 .43	64 2.52	4 .16
92 3.62	M 16	-	25 .98	32 1.26	40 1.57	50 1.97	63 2.48	80 3.15	-	-	19 .75	24 .94	43 1.69	11 .43	64 2.52	4 .16
108 4.25	M 12	M 16	25 .98	32 1.26	40 1.57	50 1.97	63 2.48	80 3.15	120 4.72	-	23 .91	30 1.18	50.5 1.99	12 .47	75 2.95	5 .20