

Coaxial Cable Connector 11_N-50-3-5/133_N

Description

Straight cable plug

Interface standards

IEC 61169-16_MIL-STD-348A/304_CECC 22210



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 11 GHz

Mechanical Data

Centre contact soldered
Outer contact clamped
Weight 0.0365 kg

Environmental Data

Operating temperature -65 °C to 165 °C
2011/65/EU (RoHS - including
2015/863 and 2017/2102) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Related Documents

Outline drawing DOU-00008106
Catalogue drawing DOU-00006125
Assembly instruction DOC-0000177464

Ordering Information

Bulk 100 pcs package 11_N-50-3-5/133_NH
Single package 11_N-50-3-5/133_NE

Additional Information

Suitable cables RADOX_RF_400, ENVIROFLEX_142, RG_400_U, RG_223_U, RG_142_B/U