



SERIES: VMS-81 | DESCRIPTION: AC-DC POWER SUPPLY

FEATURES


- up to 80 W continuous power
- universal input (90~260 Vac)
- single output from 5~36 V
- input to output 2MOPP
- active power factor correction
- over voltage and over current protections
- full medical safety approvals
- efficiency up to 85%



| MODEL | output voltage | output current | output power | ripple and noise ¹ | efficiency ² |
|-----------|----------------|----------------|--------------|-------------------------------|-------------------------|
| | (Vdc) | max (A) | max (W) | max (mVp-p) | typ (%) |
| VMS-81-5 | 5 | 14.0 | 70 | 50 | 74 |
| VMS-81-7 | 7 | 11.43 | 80 | 70 | 79 |
| VMS-81-9 | 9 | 8.89 | 80 | 90 | 81 |
| VMS-81-12 | 12 | 6.66 | 80 | 120 | 81 |
| VMS-81-15 | 15 | 5.33 | 80 | 150 | 81 |
| VMS-81-18 | 18 | 4.44 | 80 | 180 | 82 |
| VMS-81-24 | 24 | 3.33 | 80 | 240 | 82 |
| VMS-81-30 | 30 | 2.66 | 80 | 300 | 81 |
| VMS-81-36 | 36 | 2.22 | 80 | 360 | 81 |

Notes: 1. Measured at full load, 90 Vac, 20MHz.
2. Measured at full load, 230 Vac. Up to 85% max.

PART NUMBER KEY



INPUT

| parameter | conditions/description | min | typ | max | units |
|---------------------------|--|------|-----|------------|--------|
| voltage | | 90 | | 260 | Vac |
| frequency | | 47 | | 63 | Hz |
| input current | at 100 Vac, full load at 240 Vac, full load | | | 1.2 0.4 | A A |
| inrush current | at 115 Vac, full load, cool start at 25 °C at 230 Vac, full load, cool start at 25 °C | | | 28 56 | A A |
| leakage current | at 240 Vac/60 Hz | | | 0.1 | mA |
| power factor correction | at 240 Vac, full load | 0.95 | | 1 | |
| no load power consumption | at 230 Vac | | | 0.5 | W |

OUTPUT

| parameter | conditions/description | min | typ | max | units |
|-------------------------|------------------------|-----|------|-----|-------|
| line regulation | full load | | | ±1 | % |
| load regulation | at 230 Vac | | | ±5 | % |
| hold-up time | at 110 Vac, full load | 16 | | | ms |
| start-up time | at 100 Vac, full load | 0.3 | | 2 | s |
| temperature coefficient | | | ±0.4 | | %/°C |

PROTECTIONS

| parameter | conditions/description | min | typ | max | units |
|-------------------------|------------------------|-----|-----|-----|-------|
| over voltage protection | recovers automatically | 112 | | 132 | % |
| over current protection | recovers automatically | 110 | | 150 | % |

SAFETY & COMPLIANCE


| parameter | conditions/description | min | typ | max | units |
|------------------------------|--|----------------|-----|-----|------------|
| isolation voltage | input to output (for 1 minute, 10mA) input to ground (for 1 minute, 10mA) | 6,653 2,121 | | | Vdc Vdc |
| isolation resistance | at 500 Vdc | 50 | | | MΩ |
| safety approvals | IEC 60601-1, EN 60601-1, UL 60601-1 | | | | |
| conducted emissions | EN60601-1-2/EN55011 class B | | | | |
| radiated emissions | EN60601-1-2/EN55011 class B | | | | |
| harmonics | EN61000-3-2 class D | | | | |
| ESD | IEC61000-4-2, contact ± 6kV/ air ± 8kV | | | | |
| radiated immunity | IEC61000-4-(2, 3, 4, 5, 6, 8, 11) | | | | |
| EFT/burst | IEC61000-4-4, ± 2kV | | | | |
| surge | IEC61000-4-5 line to line: ± 1kV, line to earth: ± 2kV | | | | |
| voltage dips & interruptions | IEC61000-3-3, IEC61000-4-11 | | | | |
| MTBF | MIL-HDBK-217F, at 25°C | 100,000 | | | hours |
| RoHS compliant | yes | | | | |

ENVIRONMENTAL

| parameter | conditions/description | min | typ | max | units |
|-----------------------|------------------------|-----|-----|------|-------|
| operating temperature | see derating curve | 0 | | 70 | °C |
| storage temperature | | -40 | | 85 | °C |
| operating humidity | | 0 | | 95 | % |
| storage humidity | | 0 | | 95 | % |
| operating altitude | | | | 3000 | m |


DERATING CURVES

Temperature Derating Curve



MECHANICAL DRAWING

units: mm[inches]



REVISION HISTORY

| rev. | description | date |
|------|-----------------|------------|
| 1.0 | initial release | 07/19/2013 |

The revision history provided is for informational purposes only and is believed to be accurate.



CUI INC[®]

Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.