



ELESA original design CFA.

3 Type

- A** 2x2 tapped inserts
- B** 2x2 bores for socket cap screws
- C** 2x2 bores for countersunk screws
- D** 2x2 threaded studs
- E** 2x threaded studs / 2x bores for socket cap screw
- F** 2x threaded studs / 2x bores for countersunk screws
- G** 2x tapped inserts / 2x threaded studs
- H** 2x tapped inserts / 2x bores for socket cap screws
- I** 2x tapped inserts / 2x bores for countersunk screws

Metric table

1		2		Dimensions in: millimeters - inches											
l_1	l_2	d_1 Thread	d_2 Bore	d_3	h_1	h_2	h_3	h_4	l_3	l_4	$m_1 \pm 0.25$	$m_2 \pm 0.25$	t_1	t_2	
39*	40	M 4	4.3	3	14	9	9.5	19	-	14	25	25.1	6.5	4.5	
1.54	1.57		0.17	0.12	0.55	0.35	0.37	0.75		0.55	0.98	0.99	0.26	0.18	
48	49	M 5	5.5	4	19	11	13	26	14	17	31	30.5	7	5.5	
1.89	1.93		0.22	0.16	0.75	0.43	0.51	1.02	0.55	0.67	1.22	1.20	0.28	0.22	
64	65	M 6	6.5	5	23	13.5	15	30	18	24	40	40	10	6.5	
2.52	2.56		0.26	0.20	0.91	0.53	0.59	1.18	0.71	0.94	1.57	1.57	0.39	0.26	
98	98	M 10	10.5	8	35	20.5	23	46	20	35	63	60	15	10.5	
3.86	3.86		0.41	0.31	1.38	0.81	0.91	1.81	0.79	1.38	2.48	2.36	0.59	0.41	

*Size 39 only available in Types A, B and C

Specification

- Plastic, Technopolymer (Polyamide PA)
 - Black, matte finish
 - Temperature resistant up to 175 °F (80 °C)
- Pin
 - Stainless steel
 - European Standard No. 1.4305 (AISI 303)
- Tapped insert / threaded stud
 - Brass, nickel plated
- RoHS compliant

Information

- see also...
- List of Hinge Types
 - Lockable Hinges EN 151.2 (with Countersunk Screws)
 - Hinges EN 151.4 (Technopolymer Plastic, with Slotted Holes)

On request

- Technopolymer (Polyamide PA), gray
- EN 151.1 with 90° swiveling range

How to order	1	Width l_1
1 2 3	2	Length l_2
EN 151-48-49-B	3	Type