	т Q Т	m		0	₩	A	7
4							4
3				LAYOUT SHOWN AS E	XAMPLE		3
	Keying Shown as ex	ample					
	CHARACTERISTICS	Connector dimension					
	-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal					
	-Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer	ØS 32.5 Max Z 31 Max / THREAD M22x1-6g	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
N	-Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories		FR Not Listed PN: 8D515W05BD			2	
	-Temperature Range : -65°C to +175°C		A 19-10-2016				_
	-Salt Spray : 500 hours		A 19-10-2016	FIIST Release			
	-Mass : 31.38 g ± 10%		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAW	MOD N°	-
	TITLE Aluminium Plug 8D series					_	
-	BASIC SERIES: 8D 5 - 15 W 05 B D SHELL TYPE : Plug with RFI Shielding		SCALE -{	General linear Tolerances:	NPRDS / PROJEC 859	Т	-
	CONTACT TYPE : Standard Crimp Contact ORIENTATION : D SHELL SIZE : 15 CONTACT TYPE : SOCKET(500 Matings)		WWW.SOURIAU.C	This document is the property of SOURIAU it must not be reproduced or			
			communicated without permission				
	PLATING : W = Olive drab Cadmium	CONTACT LAYOUT : 15-05		SOURIAU		SHEET	
		7	A3	8D515W	05BD-C	1/2	
	H G F I	E	D	C	В	А	

	Ŧ	۵	г	m	D	0
4		Contact Layout $ \begin{array}{c} & & & \\ & & \\$				
		X-axis (mm) Y-axis (mm) +.000 (0.00) +.100 (2.54) +.174 (4.42) +.024 (0.61) +.094 (2.39) 148 (3.76) 094 (2.39) 148 (3.76) 174 (4.42) +.024 (0.61)				
ω						
						SOURIAU shall not be liable for an due to a use of the Products w the Specifications issued by either o (professional recommenda
N					A 19-10-202	Count FR PN: 8D515 16 First Release
_					ISS DATE Designed By: TITLE	Latest modification - by Date: Alumin
-					SCALE NA	General linear Tolerances:
					FORMAT A3	J WWW.SOURIAU. SOURIAL 8D515W
	Н	G	F	E	D	С

Β		A	_			
			4			
			3			
any non-conformit which does not co r of the Parties or b dation, technical n ntry Jurisc R SW05BD	mply with by a third party		2			
	CUSTOMER DRAWI	MOD N°	-			
inium Plug 8D series						
r	NPRDS / PROJECT 859					
.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission						
U DRG N° SHEET N05BD-C 2/2						
В		А				