

XZCR1111064D03

Telemecanique Safety light curtains XUSL,
Series connection jumper, 2 straight M12,
Female/Female con., 0.3 m, 5 pins



Main

Range of Product	Telemecanique Safety light curtains XUSL
Accessory / Separate Part Type	Jumper cable
Accessory / separate part category	Connection accessory
Accessory / separate part destination	Safety light curtain master/slave XCSR RFID safety switch

Complementary

Product Compatibility	XUSL2 XC SRC.2M12 XUSL4
Connector type	M12 female 5 pins straight
Wire insulation material	PUR
Collar material	Nickel plated brass
Cable outer diameter	0.20 in (5 mm)
Cable composition	5 x 0.34 mm ²
Cable length	0.98 ft (0.3 m)

Environment

IP Degree of Protection	IP67 IP65 IP69K
-------------------------	-----------------------

Ordering and shipping details

Category	22483-MACHINE CABLES
Discount Schedule	DS3
GTIN	3389119620505
Nbr. of units in pkg.	1
Package weight(Lbs)	1.41 oz (40.0 g)
Returnability	No
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	0.98 in (2.5 cm)
Package 1 width	3.15 in (8 cm)
Package 1 Length	6.69 in (17 cm)
Unit Type of Package 2	S02
Number of Units in Package 2	40
Package 2 Weight	4.21 lb(US) (1.911 kg)
Package 2 Height	5.91 in (15 cm)

Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes