



Click [here](#) for the 3D model.

Dimensions

| | |
|----|----------------------|
| D | 6.35mm +/-0.38mm |
| L | 12.7mm +/-0.51mm |
| LL | 38.1mm MIN |
| F | 0.64mm +0.1/-0.025mm |

Packaging Specifications

| | |
|--------------------|-----------|
| Packaging | Bulk, Bag |
| Packaging Quantity | 25 |

General Information

| | |
|-------------|--|
| Series | LDD Comm COG |
| RoHS | No |
| Prop 65 | ⚠ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov . |
| SCIP Number | 132e61c0-5a2b-4355-a818-8e6ea80949b5 |
| Termination | Lead (SnPb) |
| AEC-Q200 | No |
| Notes | Lead Length Shown Is For Parts Supplied In Bulk, See Packaging Specifications For Lead Lengths When Not Provided In Bulk. |

Specifications

| | |
|---------------------------------|----------------|
| Capacitance | 0.01 uF |
| Capacitance Tolerance | 10% |
| Voltage DC | 200 VDC |
| Dielectric Withstanding Voltage | 500 VDC |
| Temperature Range | -55/+125°C |
| Temperature Coefficient | COG |
| Dissipation Factor | 0.1% 1 kHz 25C |
| Insulation Resistance | 100 MOhms |